INDEXES TO THE JOURNAL

Compiled by

THE AMERICAN CERAMIC SOCIETY, INC.

ROSS C. PURDY, *Editor*
EMILY C. VAN SCHOICK, *Assistant Editor*

Vol. 27 December 1, 1944 No. 12

AUTHOR INDEX

The reference number in parentheses refers to the *monthly* issue of the *Journal;* the numbers following are the *page* numbers.

Allen, Dan. See Galbreath, W. W., Jr.; McVay, T. N.
Amberg, C. R. Effect of additions of diopside on properties of wall-tile body, (11) 324–26.
Andrews, A. I. See Blanchard, M. K.; Fréchette, V. D.; Petersen, F. A.
Andrews, A. I., and Swift, H. R. Effect of composition and temperature on solubility of iron oxide in ground-coat enamel glass, (2) 46–50.

Baumann, H. N., Jr. Fusion experiments in system MgO–FeO–Cr_2O_3–Al_2O_3, (11) 327–29.
Beals, M. D., and Zerfoss, Samuel. Volume change attending low-to-high inversion of cristobalite, (10) 285–92.
Birch, R. E., and Hall, M. P. Some factors affecting P. C. E. of silica fire clay, (8) 239–41.
Bishop, F. L., Jr. Surface layer of sheet glass, (5) 145–48.
Blanchard, M. K., and Andrews, A. I. Enamel film strength as affected by properties of enamel before, during, and after drying, (1) 25–31; Fundamental properties of soluble salts in enamel mill liquors, (1) 17–24.
Blanchard, M. K. See Harman, C. G.
Blount, E. B. See Pence, F. K.
Brookover, George. See Potts, J. C.
Burch, O. G. See Potts, J. C.
Burnham, Forrest, and Harder, C. M. Practical production of one-fire luster glazed pottery, (2) 62–64.

Carter, H. D. See King, B. W., Jr.
Cohn, Gunther. Significance of topochemical factors on rate of reactions between solid salts, (10) 308–16.
Coughanour, W. L., and Utter, J. L. Cataphoresis of purified fractionated kaolinite particles, (4) 116–20.

Draker, H. C. See King, B. W., Jr.

Fabianic, W. L. Glasshouse stones, (11) 330–50.
Falcão, E. de R. See Scholes, S. R.
Fraser, W. A., and Upton, L. G. Optical fluor-crown glasses, (4) 121–28.
Fréchette, V. D., and Andrews, A. I. Investigation of reactions of simple magnesia spinels with alkaline earth orthosilicates in solid state, (7) 197–202.

Galbreath, W. W., Jr. See McVay, T. N.
Galbreath, W. W., Jr., McVay, T. N., and Allen, Dan. Lightweight superduty kyanite-topaz refractory, (8) 241–46.
Ghering, L. G. Refined method of control of cordiness and workability of glass during production, statistical control charts applied to daily measurements of density, (12) 373–87.
Ghering, L. G., and Knight, M. A. Properties and diagnosis in pressed and blown glassware, (9) 260–66.
Glass Container Association Ring Section Sub-Committee of Standard Testing Procedure Committee. Polariscopic examination of glass-container sections, (3) 85–89.
Goudge, M. F. Brucite magnesia, (1) 8–10.
Grim, R. E., and Rowland, R. A. Differential thermal analysis of clays and shales, and control and prospecting method, (3) 65–76.

Hall, M. P. See Birch, R. E.
Harder, C. M. See Burnham, Forrest.
Harman, C. G. Suggestions for solution of difficult glaze-fit problem, (8) 231–33.
Harman, C. G., and Blanchard, M. K. Study of factors involved in glaze-slip control, correlation of glaze thickness with air permeability, II, (7) 207–209.
Harman, C. G., and Johnson, H. C. Study of factors involved in glaze-slip control, additional glazes and improved technique and apparatus, III, (7) 209–14; practical uses for coherence value and receptivity measurements, IV, (7) 214–20.
Harman, C. G., and Schaefer, C. F. Study of factors involved in glaze-slip control, glaze-slip specifications, I, (7) 202–207.
Hausner, H. H. Influence of humidity on dielectric properties of high-frequency ceramics, (6) 175–81.
Herman, A., and Shay, H. L. Effect of glass on alcoholic products stored in bottles at room temperature for three years, (2) 53–57; correction, (12) 401.
Huggins, M. L., and Sun, K.-H. Changes of properties of glass resulting from changes of composition, (1) 10–12; Glass properties and the periodic table, (1) 13–17.
Hunt, H. J. Analysis of batch for segregation, (10) 305–308; see also Zarbo, G. J.
Hutchison, Clark. Abrasion resistance of porcelain enamels, (12) 366–69.

Johnson, A. G., and Underhill, D. B. Quantitative determination of the glassy phase in a ceramic body, (2) 40–41.
Johnson, A. L. See Norton, F. H.
Johnson, H. C. See Harman, C. G.

King, B. W., Jr., Carter, H. D., and Drake, H. C. Properties of enamel slips, general properties of clays and enamel slips, I, (9) 253–60.
King, R. M. Mechanics of enamel adherence, influence of manganese dioxide on metal precipitation at ground coat-iron interface, XVI, (11) 350–51.
Kingslake, R. Optical glass from viewpoint of lens designer, (6) 189–95.
Knight, M. A. Surface tension and persistence of cords in glass, (5) 143–45; see also Ghering, L. G.

Lamar, R. S. Particle shape and differential shrinkage of steatite talc bodies, (11) 317–20.
Lauck, F. W. See Martin, W. G.
Lawrence, W. G. See Norton, F. H.
Lyon, K. C. Calculation of surface tension of glasses, (6) 186–89.

Marquis, John. Cone 01 glazes for low-temperature vitreous ware, (12) 358–66.
Martin, W. G., and Lauck, F. W. Observations indicating absence of plastic flow in glass coating on steel, (11) 352–54.
McCutchen, E. S. Strontia and its properties in glazes, (8) 233–38.
McDevit, W. F. Effect of firing atmosphere on development of colors in ceramic glazes, (6) 165–75.
McVay, T. N. See Galbreath, W. W., Jr.
McVay, T. N., Galbreath, W. W., Jr., and Allen, Dan. Substitution of topaz, domestic kyanite, and synthetic corundum for India kyanite, raw topaz as high-temperature bond for domestic kyanite, IV, (9) 275–82.
Mohr, W. C. See Russell, Ralston, Jr.

Nordberg, M. E. Properties of some Vycor-brand glasses, (10) 299–305.
Norton, F. H., and Johnson, A. L. Fundamental study of clay, nature of water film in plastic clay, V, (3) 77–80.
Norton, F. H., Johnson, A. L., and Lawrence, W. G. Fundamental study of clay, flow properties of kaolinite-water suspensions, VI, (5) 149–64.
Noyes, Bradford, Jr. See Taylor, N. W.

Owens-Illinois Glass Company General Research Laboratory. Effect of fluorine and phosphorus pentoxide on properties of soda-dolomite lime-silica glass, (12) 369–72; Effect of substituting MgO for CaO on properties of typical soda-lime glasses, (8) 221–25.

Pence, F. K., and Blount, E. B. Vermiculite as raw material in ceramic manufacture, (2) 50–52.
Petersen, F. A., and Andrews, A. I. Enamel Utensil Manufacturers' Council tentative standards solubility test for porcelain enameled cooking utensils, (4) 113–15.
Peterson, C. A. See Robinson, H. A.
Pole, G. R. Calcination of topaz ore in rotary kiln, (6) 181–85.
Potts, J. C., Brookover, George, and Burch, O. G. Melting rate of soda-lime glasses as influenced by grain sizes of raw materials and additions of cullet, (8) 225–31.

Robinson, H. A., and Peterson, C. A. Viscosity of recent container glass, (5) 129–38.
Rowland, R. A. See Grim, R. E.

Russell, Ralston, Jr., and Mohr, W. C. Casting characteristics of clays, improved methods for determination, I, (4) 97–113.
Russell, Ralston, Jr., and Weisz, R. S. Some particulate characteristics of commercial flint and feldspar, (1) 1–7.

Schaefer, C. F. See Harman, C. G.
Scholes, S. R., and Falcão, E. de R. Rapid method for estimating soda in glasses, II, (5) 148.
Schramm, Edward. Glost kiln refractories, (9) 282–84.
Seabright, E. C. Methods for testing cleaner solutions, (3) 90–95.
Shay, H. L. See Herman, A.
Silverman, W. B. See White, J. F.
Smith, D. C. See Zarbo, G. J.
Sun, K.-H. See Huggins, M. L.
Swift, H. R. See Andrews, A. I.

Taylor, N. W., and Noyes, Bradford, Jr. Aging thermometers, (2) 57–62.
Thiemecke, H. Notes on moisture expansion, (12) 355–58.
Tiede, R. L. See Tooley, F. V.
Tooley, F. V., and Tiede, R. L. Factors affecting degree of homogeneity of glass, (2) 42–45.
Tracey, J. I., Jr. High-alumina clays of Pulaski and Saline counties, Ark., (8) 246–49.

Ueltz, H. F. G. Crystalline and glassy phases of steatite ceramics, (2) 33–39.
Underhill, D. B. See Johnson, A. G.
Upton, L. O. See Fraser, W. A.
Utter, J. L. See Coughanour, W. L.

Weisz, R. S. See Russell, R., Jr.
White, J. F., and Silverman, W. B. Devitrification characteristics of alkali-lead oxide-dolomite lime-silica glasses, (3) 81–85.
White, J. S. Particle-size distribution of steatite talc, (11) 320–23; for correction see (12) 401.
Winter, Aniuta. Time problem in annealing (9) 266–74.

Zapffe, C. A. Conversion of certain refractory oxides to a suboxide form at high temperatures, (10) 293–98.
Zarbo, G. J., Hunt, H. J., and Smith, D. C. Analysis of cords and stones, (5) 138–42.
Zerfoss, Samuel. See Beals, M. D.

SUBJECT INDEX TO THE JOURNAL

Volume 27, 1944

The reference number in parentheses refers to the *monthly* issue of the *Journal;* the number following is the *page* number.

Abbe values for pure oxides, curves and equation for calculation, (1) 15–16.
Abramson formula for particle concentration, (4) 117.
Abrasion resistance of porcelain enamels, (12) 366.
Achromatism in optical glass, description, proportionality, and diagram of method, (6) 189–91.
Acid solubility, test for enameled utensils, tentative standard test of E. U. M. C., (4) 113.
Acid tests for luster glazes, (2) 64.
Adams and Williamson equation for relation of reciprocal of stress with time, (2) 58.
Air-separator method. See *Methods.*
Alcoholic products, hydrogen-ion concentration of, effect of commercial bottles after storage for three years at room temperature, (2) 53.
Alkaline earth orthosilicates in solid state, reaction of simple magnesia spinels with, (7) 197–202; optical properties, (7) 199.
Alkalinity of cleaner solutions, equations for calculation, (3) 91.
Alumina and silica in glass, semimicro-determination method for analysis, tables, (5) 139–41.
Alumina clays, high-alumina clays in Ark., deposits, chemical analyses, geologic history, and availability, (8) 246–49.
American Society for Testing Materials, standard method, mechanical analysis of soils. See *Methods, hydrometer.*
Anastigmat lenses, design, (6) 194; see also *Glass, optical.*
Andreasen pipette method. See *Methods.*
Annealing of glass. See *Glass.*
Apparatus, air separator, laboratory type, for particle-size measurements, (11) 320.
for atmosphere control in furnaces for ceramic glazes, (6) 166–67.
Babinet compensator for measuring stresses in glass, (3) 85.
for $BaSO_4$ and quinolate filtration and micro-oven assembly, (5) 151.
dilatometer for volume-expansion tests on cristobalite, (10) 287.
drier and stirrer for clays for slip preparation, (4) 99.
for enamels, for solubility tests on enameled utensils, (4) 114–15.
furnaces. See *Furnaces.*
for glass, stones and cords in, semimicro-determination, (5) 141.
for glass surface-tension measurements, diagram, photo, (5) 145–46.
for glaze-coherence tests, diagram, (7) 204; for measuring coherence values and body receptivity, photo, (7) 210.
for glaze slips for surface-tension measurements, diagram, (7) 204.
for glaze-thickness tests, mechanical dipper, (7) 208.
for glazes, constant heating schedules, (6) 167.
homogeneity equipment for tests on soda-lime-silica glass, photo, (2) 42; centrifuge head, diagram, (2) 43.
Apparatus, (*continued*)
hydrometers. See *Hydrometers.*
MacMichael viscosimeter, modified, for data on kaolinite-water suspensions, (5) 158–63.
microscope, polarizing, for examination of glass-container ring sections, (3) 88.
for particle-size measurements, (11) 320–21.
for permeability, casting rate, and water retention of clays, (4) 99–100.
for semimicro-determination of stones and cords in glass, (5) 141.
Stormer viscosimeter for thixotropy tests, (4) 99.
viscometers, viscosimeters. See *Viscosimeters.*
for volume-expansion tests on cristobalite, (10) 287; expansion bulb and thermocouple, photo, diagram of furnace and expansion bulb, (10) 288.
for water-film thickness of plastic clays, mold cross section, (3) 78.
Arkansas clays. See *Clays, high-alumina.*
Arrhenius exponential law for viscosity of suspensions vs. concentration, (5) 151.
Autoclaves for chemical durability of glass bottles, (2) 54.
steam tests on talc-pyrophyllite bodies, tables, (12) 356.
test results on glazes for low-temperature vitreous ware, (12) 364.

Balinkin equation for evaluation of small overall color differences, (6) 166.
Barium chloride–H_2O, equilibrium system, diagram, (1) 21; $BaCl_2$–$MgCl_2$, equilibrium system, diagram, (1) 23.
Barium fluoride–$BaCl_2$, equilibrium system, diagram, (1) 23.
Barium orthosilicate, synthesis, tables, and reaction test, (7) 200–201.
Batch, glass. See *Glass, batch.*
Batch stones in glass. See *Glass, cords and stones; Stones.*
Bausch and Lomb Optical Co., optical glass types and characteristics, (6) 190.
Bibliography of chemical reactions, (1) 23–24.
of equilibrium systems, (1) 24.
glass, devitrification and stone developments, (11) 350.
Bisque bodies and glazed semivitreous ware, moisture-expansion studies, curves, (12) 355–57.
Blisters and coloring material in bottle glass, source, detection, photomicrograph, (11) 348.
Bottles, glass. See *Glass, bottles; Stones.*
Brewsterian angle, apparent, Pfund method for determination, (5) 145.
Brucite magnesia, sources, characteristics of granular product, uses, (1) 8–10.
Brucitic limestone, description and processing, (1) 8.
Büchner funnel vs. cup-casting method for casting slip, (4) 111.

Calcination of topaz ore in rotary kiln, (6) 181–85.
Calcium chloride–H_2O, equilibrium system, diagram, (1) 20.
Calcium chromate, thermal decomposition, reactions, (6) 169.
Carman's permeability method, rate of flow, (11) 319.
Casagrande hydrometer method, (11) 320.
Casting characteristics of clays, improved methods, (4) 97; see also *Slips.*
Cataphoresis of purified, fractionated kaolinite particles, ultramicroscopic method, (4) 116.
Ceramic ware, glassy phase, method of determination, (2) 40.
Charts, statistical control, for daily density measurements of glass, (12) 373–87.
Chemical reactions. See *Reactions.*
Chinaware, hotel, and semivitreous dinnerware, body composition, glaze coherence, and receptivity test data, (7) 211–13; see also *Dinnerware; Vitreous ware.*
Chrome-corundum, FeO and MgO additions, effect of Cr_2O_3-Al_2O_3 content, curves, (11) 329; effect of varying Cr_2O_3 and MgO fused with Al_2O_3, (11) 329.
fusion studies, effect of varying MgO and SiO_2, curves, (11) 328; effect of adding TiO_2, (11) 328.
Chrome-lime, mixtures, colors when calcined at various atmospheres, diagram, (6) 168.
Chrome ore, mineral composition, (11) 327.
Chrome refractories, effect of chemical and thermal treatment, (11) 327.
Chrome–tin system, colors developed in, (6) 174.
Chromium oxide–Fe_2O_3, X-ray studies, (6) 173.
Clay plants, operating pits, thermal analyses of clays, control method, (3) 65.
Clay stones. See *Stones.*
Clays. See also *Kaolin.*
ball, for slip casting, effect of electrolyte content, curves and data, (4) 109–11.
casting characteristics, improved methods, (4) 97.
clay-flint-feldspar bodies, moisture-expansion data, (12) 357.
clay minerals, kaolinite, hydrated halloysite, illite, and bentonite, thermal reactions, curves, (3) 67.
clay minerals, pure forms and synthetic mixtures, method for differential thermal analyses, (3) 65.
clay suspensions, flow properties of kaolinite-water suspensions, (5) 149.
clay suspensions, for study of cataphoretic velocity of purified fractionated kaolinite particles, (4) 116.
for common brick, thermal curves, (3) 75.
for enamel slips, physical and chemical properties, (9) 253–54; carbon content and opacity data, (9) 257.
in enamels, fired, properties, (9) 257–58.
fundamental studies, nature of water film in plastic clays, V, (3) 77; flow properties of kaolinite-water suspensions, VI, (5) 149.

Clays (*continued*)
Georgia, thermal curves for bauxitic kaolin, soft, hard, and plastic kaolins, and fuller's earth, (3) 71–73.
German glasspot, thermal curves, (3) 73.
gibbsite, boehmite, diaspore, quartz, calcite, dolomite, and gypsum, thermal reactions, curves, (3) 68.
for glazes, base-exchange capacity vs. coherence value, curve, (7) 219.
high-alumina, Ark., location and description of deposits, (8) 246; chemical analyses, geologic history, and availability, (8) 247–49.
hydrogen-ion vs. NaOH concentration, curves, (9) 254.
Illinois, thermal curves for kaolin and fire clays, (3) 71, (3) 73–74.
Missouri burley flint and plastic fire clay, thermal curves, (3) 71, (3) 73.
natural, thermal curves, (3) 71.
Ohio, thermal curves for flint, ball, and fire clays, (3) 71, (3) 73.
organic materials and minerals in, clarain, vitrain, limonite, marcasite, pyrite, and goethite, thermal reactions, curves, (3) 69.
permeability, casting rate, and water retention, test apparatus, (4) 99–100.
settling tests, maximum particle-diameter data, (9) 255.
and shales, differential thermal analysis, (3) 65; thermal curves, vertical scales for temperature-difference data, (3) 67, see also *Shales*.
for slips, drier for moisture compensation and stirrer, (4) 99.
for slips, enamel, general properties, (9) 253.
in slips, single clays and in combination, properties, (9) 258–60.
synthetic mixtures, thermal curves, (3) 70.
Tennessee ball, for glaze slips, coherence and surface-tension values, curves, (7) 205–206.
Tennessee, sagger and wad, thermal curves, (3) 72.
Texas, for glaze slips, coherence and surface-tension value curves, (7) 205–206.
water film in, simple clay–water system, water-film thickness and stability tests, (3) 77–79.
X-ray patterns, (9) 254.
Clayware, clay-vermiculite bodies, effect of temperature on properties, thermal-expansion data at cone 08, tables, (2) 52.
dust-pressed and plastic processes for bodies with vermiculite as raw material, properties and comparison of bodies, table, (2) 50–51.
structural, thermal-conductivity and sound-absorption measurements, effect of vermiculite in, (2) 50–51.
Cleaner solutions, "activity factor" or "available alkali" formulas, (3) 90; available alkali, calculated percentage daily results, (3) 92.
alkalinity and sodium hydroxide content, formulas for calculation, (3) 91–93.
for enamel industry, test methods, soap test and free alkali and soluble soap test, (3) 90–91; sheet cleaning, cleaner strength, available alkalinity and soap and free-alkali tests, (3) 93–95.
Cobalt oxide with Ni_2O_3 and MnO_2 in enamels, effect on metal precipitation at ground coat-iron interface, (11) 350–51.
Coherence values for slip glazes. See *Glazes; Slips*.
Colors, brown, composition and reflectance measurements, (6) 173–74.
in ceramic glazes, effect of firing atmosphere, (6) 165.
color equivalents in flint glass, with and without tint plate, (3) 87.
designation, hue, lightness, saturation, definitions, (6) 165.
of glazes, measurement, process, (5) 168; see also *Glazes*.
green, for ceramic glazes, data and curves, (6) 168–71.
hue and saturation, color diagram for reflectometer data, (6) 166.
pink and maroon, compositions and effect of firing atmosphere, (6) 174–75.
yellow, compositions and reflectance measurements in various firing atmospheres, curves and table, (6) 172–73.
Container glass. See *Glass bottles; Glass container*.
Cooke triplet lens, diagram, (6) 192.
Cooking ware, porcelain enameled utensils, tentative standard solubility tests of E. U. M. C., diagrams of solubility apparatus, punch and die, position of test
Cooking ware, porcelain enameled (*continued*) units on hot plate, and electrical wiring equipment, (4) 114–15.
Copperheads in enamels. See *Enamels*.
Cordierite body, glaze-fit, composition, (8) 233.
Cordiness in glass, refined method of production control, (12) 373.
Cords and stones in glass. See *Glass, cords, cords and stones; Stones*.
Corning Glass Works, optical glass types and characteristics, (6) 190.
Cristobalite, expansion measurements, heating and cooling cycles, (10) 289; hysteresis effect of inversion and inversion temperature and volume change, (10) 289–90; expansion test samples, properties and inversion data, (10) 290–91.
and tridymite as source of stones in bottle glass, (11) 343; cristobalite and devitrite as source, (11) 346–47.
volume expansion in low-to-high inversion change, (10) 285.
Crystals, topochemically disordered, (10) 312.
Cullet for glass. See *Glass, cullet*.
Cup-casting rate determination for tests on casting slips, (4) 102.

Debye and Huckel formula for particle concentration, (4) 117.
Decomposition, thermal, effect on reactivity in magnesium formation, (10) 313.
Definitions, cords in glass, meaning to workmen, packing room, laboratory, and optical industry, (9) 260–61.
dielectric constant, equation for, (2) 34.
differential shrinkage, (11) 317.
dispersive power, (6) 189.
electrical terms, (6) 180.
glossary of symbols and terms for density measurements of glass, (12) 375.
hue, (6) 165.
judd, (6) 166.
lightness, (6) 165.
photoelastic constant, (3) 87.
power factor and Q factor for dielectric body, (2) 34.
refractive index, (6) 189.
saturation, (6) 165.
specific shape factor, (11) 317.
steatite, derivation and formula, (2) 33.
stress-optical coefficient, (3) 87.
thixotropy, (5) 154.
units and symbols for study of flow of suspensions, (5) 150.
Density of glass. See *Glass, density*.
Devitrification of alkali-lead oxide-dolomite lime-silica glasses, (3) 81.
Devitrification stones in glass. See *Stones*.
Devitrite and cristobalite as source of stones in glass, description and photomicrographs, (11) 346–47.
Dictionaries, cited, applied physics, (6) 190.
chemical solubilities, (1) 23.
inorganic chemical reactions, (1) 24.
Dielectrics, dielectric constants and loss factor in glassy bodies, tables, (2) 37.
dielectric materials, effect of humidity on power factor, data, (6) 177.
dielectric properties of high-frequency ceramics, effect of humidity, factors affecting, (6) 175–76.
steatite, crystalline and glassy phases, (2) 33.
Differential thermal analysis. See *Thermal analysis*.
Dilatometer for tests on volume expansion of cristobalite, (10) 287.
Dinnerware. See also *Chinaware; Glazes; Vitreous ware*.
glazes, strontia substitutions in, (8) 234.
glost, kiln refractories for firing, (9) 282.
Diopside, additions in wall-tile body; effect, firing and thermal-expansion data, curves, glaze trial results, and absorption and moisture expansion of bodies fired at different P.C.E., (11) 324–26.
as source of stone in bottle glass, description and photomicrographs, (11) 345–46.
Dispersion constants and specific dispersion constants, diagrams and equations, (1) 15–16.

Earths, fuller's, Ga., thermal curves, (3) 73.
Eastman Kodak Co., optical glass types and characteristics, (6) 190.
Einstein theoretical law for suspension of spheres, (5) 151.
Electrical data on steatite dielectric test bodies, (2) 37.
Electrical porcelain. See *Porcelain*.
Electrolytes in casting slips, effect on kaolin and ball-clay content, curves, (4) 107–108, (4) 110.
effect on permeability of kaolin in casting slips, curves, (4) 100.
in glaze slips, effect of Na_2CO_3, curves, (7) 218.
Enameled Utensil Manufacturers' Council. See *Cooking ware*.
Enamels, abrasion resistance, abrasion indices of commercial bodies, visual ratings, and effect of SiO_2 content, (12) 367–68.
adherence mechanics, effect of manganese dioxide on metal precipitation at ground coat-iron interface, (11) 350–51.
clays for, carbon content vs. scattering coefficient of fired enamel, curve, (9) 256; carbon content and opacity data, (9) 257.
cleaner solutions, test methods, (3) 90.
commercial, abrasion-resistance tests, (12) 367–68.
copperheads in, effect of solubility temperature coefficient, (2) 50.
cracking tendency, effect of shrinkage and film drying behavior, (1) 26.
drying behavior, effect of soluble salts, (1) 17.
enameling iron, sheet-cleaning tests, cleaner strength and available alkali tests, (3) 91.
films and film strength, cracking tendency, effect of soluble salts, (1) 25–26; film drying behavior and shrinkage characteristics, (1) 26; packing density, effect of tearing, (1) 29; firing effect, (1) 31.
fired, clays in, properties, (9) 257–58.
frits. See *Frits*.
glass coatings on steel, absence of plastic flow in, studies, (11) 352.
iron oxide solubility, batch composition, effect of composition and temperature, (2) 46; batch weights and oxides, effect of composition, table and curves, (2) 48–49.
metal-cleaning solutions. See *Cleaner solutions*.
metal precipitation in, effect of cobalt and nickel on fired ground coats, (11) 350; at ground coat-iron interface, effect of manganese dioxide, (11) 350.
mill liquors, soluble salts in, properties, (1) 17; physicochemical behavior and possible chemical reactions, (1) 21–22.
opacity, vs. carbon content, for enamel slips, (9) 257.
porcelain, abrasion resistance, (12) 366.
porcelain, solubility test for cooking ware, (4) 113.
reflectance data, effect of carbon content and opacity of clays for, (9) 257.
sheet-steel ground-coat, solubility of iron oxide in, effect of composition and temperature, (2) 46.
shrinkage and film drying behavior, effect on cracking tendency, (1) 26.
silica content, effect on abrasion resistance, (12) 367–68.
slips, application of studies on clay, water, and electrolyte systems, (1) 25.
slips, clays for, pickup data on frits, diagrams, (9) 256–57; single clays and combined, properties, (9) 259–60; see also *Slips*.
solubility of iron oxide, batch and base compositions and composition limits, (2) 46–47; effect of composition on solubility of iron and ferric oxides, (2) 49.
soluble salts in, specific types, effect on tearing, (1) 30; see also *Soluble salts*.
tearing, visual observations during firing, (1) 25; packing density of dried enamel film, effect, (1) 29; effect of specific salts, (1) 30; relation of variables in, chart, (1) 31.
Equilibrium diagrams, liquidus isotherms for CaO·MgO glasses, (3) 84.
phase diagrams of CaO·MgO glasses with 12% and 16% Na_2O, (3) 83.
Equilibrium systems, bibliographies cited, Hall and Insley and Landolt, Börnstein, and Roth, (1) 24.
binary, of soluble salts, primary and derived, (1) 22–24.
possible chemical reactions between soluble salts in enamel mill liquors, (1) 22.
salt–water, diagrams, (1) 20–21.
Expansion, apparatus for tests, expansion bulb, thermocouple, furnace, and dilatometer, (10) 287–88.
cristobalite test samples, properties, (10) 290; inversion data on samples, (10) 291.
moisture, of bisque and glazed semivitreous bodies, curves, (12) 356–57.

Expansion (*continued*)
moisture, of wall-tile bodies with diopside additions, (11) 326.
silica inversions, sluggish and low-to-high types, (10) 285.
thermal, in soda-lime-silica glass, factors for calculation, (9) 262.
volume, of cristobalite in low-to-high inversion, (10) 285.

Feldspar, coarse-grained, as source of stones in glass, (11) 339.
as flint substitute in casting slips, (4) 106–107.
and nepheline syenite, particle-size data, (1) 5.
particle-size variations, effect on electrical porcelain body, (1) 1; data and curves for apparent distribution, (1) 6.
and talc, diopside substitutions for, in wall-tile body, (11) 324.
Ferric oxide-Cr_2O_3, X-ray studies, (6) 173.
Ferric oxide solubility in enamel glasses. See *Enamels, iron oxide solubility.*
Fick's laws of diffusion, (7) 197.
Film strength of enamels. See *Enamels*
Fire-control instruments, glass for, aplanatic properties, (6) 192.
Fire polish of sheet glass, nature of and measurements, (5) 145.
Flint, commercial, particle-size data, variations in, effect on electrical porcelain body, (1) 1; different grades, logarithmic-probability plot, data, curves, (1) 5.
feldspar as flint substitute in casting slips, (4) 106–107.
Flint glass. See *Glass.*
Florida kaolins. See *Kaolins.*
Flow of glaze slips, flow-stress curve, (7) 203.
of suspensions, units and symbols for study, (5) 150; properties in anisotropic particles, (5) 151; mechanism, effect of variations of concentration, particle size, rate of shear, and surface activity, (5) 156.
Fluor-crown glass, optical properties of, effect of variations in composition, (4) 121; tabular data, (4) 124–25.
Fluorine in glass, effect of B_2O_3 on properties, (4) 126.
in glass as SiO_2 substitute, effect and curves, (12) 369–70; chemical analysis and measured properties, (12) 370.
Forsterite, synthesis, table and reaction test, (7) 200–201.
Freezing process for annealing glass. See *Glass, annealing.*
Fresnal equations for reflecting power of dielectric, (5) 145.
Frits, enamel, clays for, pickup data, diagrams, (9) 256; pickup values vs. clay blends, curves, (9) 258–59.
ferric oxide in, effect on refractive index, curves, and effect of temperature on solubility, (2) 47.
for low-temperature vitreous ware, batch formulas, (12) 360.
Fulcher equation for measuring viscosity of glass, and constants for Fulcher equation, (5) 135–36.
Fuller's earth. See *Earths.*
Furnaces. See also *Kilns.*
atmosphere control for firing ceramic colored glazes, diagrams, (6) 166–67.
for differential thermal analyses of clays and shales, photo and wiring diagram, (3) 66.
electric, for fusion tests on chrome ore, (11) 327.
electric resistance, for atmosphere control in firing colored ceramic glazes, (6) 167.
for expansion tests on cristobalite, dilatometer, photo, (10) 287; furnace diagram and expansion bulb, (10) 288.
glass, assembly diagram for melting-rate tests, (8) 225.
glass, effect of furnace size on density values, (12) 382.
glass, refractories failures in, as source of stones, photos, (11) 331–37.
glass, stone prevention in, (11) 334.
heating chamber for measurement of electrical properties of steatite dielectrics, diagram, (2) 36.
heating rate, apparatus for constant schedules, (6) 167.
for viscosity tests on glass, high-temperature, diagram, (5) 136.
Fused quartz, glazed porcelain, and plate glass, surface resistivity vs. relative humidity, curves, (6) 179.
Fusion tests in system MgO–FeO–Cr_2O_3–Al_2O_3, (11) 327.

Georgia clays. See *Clays; Earths.*
Glass, Abbe values for pure oxides, diagram, (1) 15.
alkali-lead oxide-dolomite lime-silica, devitrification studies, raw materials and oxide compositions, (3) 81; composition, liquidus temperature, and primary pnases, table, (3) 82; phase diagrams and liquidus isotherms, (3) 83–84.
alumina in, semimicro-determination method for, tables, (5) 140–41.
annealing and aging, for thermometers, Adams and Williamson equation, (2, 58.
annealing, effect on density, (9) 261.
annealing, freezing method and discontinuous freezing process, (9) 271–73.
annealing, time problem, annealing schedule, (9) 266–68; time allowance, required refractive index, (9) 273–74.
aplanatic properties in lens for fire-control instruments, (6) 192.
batch for, analysis for segregation, effect of cullet, (10) 305–306.
batch, miniature batch for comparisons, effect, (10) 307–308.
boric oxide in, effect on fluorine-containing glasses, (4) 126.
borosilicate thermometer bulb, refractive index of glass vs. thermometer reading change from aging of bulb, curve, (2) 58.
bottles for alcoholic products, effect on pH after storage three years at room temperature, (2) 53; correction, (12) 401.
bottles, autoclave chemical durability tests, pH concentration vs. chemical durability, curves, (2) 54–55.
bottles, spectroscopic studies, metallic contamination in commercial glass vs. Pyrex-brand glass, (2) 53.
bottles, stones in. See *Stones.*
chemical resistance to H_2O and H_2SO_4 with MgO replacements for CaO, (8) 222.
colored, blisters in, source and photomicrographs, (11) 348–49.
commercial lime crystal, devitrification studies, (3) 81.
component changes in, equations for calculation, (1) 10.
composition changes in, effect on refractive index, table, (1) 12.
container, viscosity studies, (5) 129; see also *Glass, viscosity.*
control-chart method for density analysis, (12) 375; utility and limitations, (12) 387.
control of production, discussion and chart, (12) 382–84.
cords, cordiness. See also *Stones.*
"cold" or "thermal," (9) 261.
composition, separation from matrix, method, (9) 264.
cord grading of ware, density values, chart, (12) 376.
floating vs. immersed cords, Jebsen-Marwedel explanation, (5) 148.
immersed cords, surface energy in, (5) 144.
mechanical strength and stresses, types, (9) 265.
in pressed and blown ware, properties and diagnosis, (9) 260.
spherical shape, as result of surface tension, (5) 143–44.
and stones in, apparatus for $BaSO_4$ and quinolate filtration and micro-oven assembly, (5) 141.
and stones in, separation by semimicro-determination method, (5) 138; typical analysis, (5) 141.
stress and density data, interpretation, (9) 265.
various meanings to workmen, packing room, laboratory, and optical industry, (9) 260–61.
"viscosity" ridges or waves, cause, (9) 261.
and workability, refined control method, (12) 373.
crystals, and pores in ceramic body, effect of cone firing and comparison of polished specimens and powder mounts, (2) 41.
cullet additions and raw materials, effect of grain size on melting rate, (8) 225.
cullet, factory-quarried, as source of stones, (11) 332; stones in flint cullet, photo, (11) 331.
cullet in, incomplete removal, effect and errors, screen tests, (10) 306–307.
density, annealing effect, data, (9) 261.
calculations, equations and volume-constant curves, (1) 13.
changes in, thermometer arrangement for studies, (2) 61.

Glass, density (*continued*)
vs. chemical analysis as control method, (12) 386.
distribution curves at various melting times, (2) 44.
effect of furnace size, (12) 382.
glossary of symbols and terms for measurement, (12) 375.
Huggins' factors for calculations, (9) 262; factors in density differences, (9) 263; Archimedes' principle and sink-float methods for density measurement, (9) 263.
level, tolerable limits, composition equivalents, (12) 383; modified control limits, (12) 384.
range, statistical character of data, (12) 385–86.
statistical control charts for measurement, (12) 373.
thermal history, effect, (9) 261.
thermometers for studies, (2) 61.
values, for average and 3-sigma limits on plant furnaces, table, (12) 377; charts, (12) 378–80.
variability of plants and furnaces measured by 3-day range of density, chart, (12) 379; discussion, (12) 382; table, (12) 387.
volume constants and equation for calculation, (1) 13.
dispersion constants, equations and curves, (1) 16.
flint, clay stones in, mullite growth, photomicrographs, (11) 336–37.
flint, color equivalents, with and without tint plate, (3) 87.
fire-control instruments, aplanatic properties, (6) 192.
fire-polished, surface-tension measurements, apparatus and methods, (5) 145–48.
fluor-crown, chemical durability, thermal expansion, (4) 127–28.
fluor-crown, effect of composition variations on optical properties, (4) 121.
fluor-crown, effect of fluorine, alumina, $AlF_3 \cdot 3^1/_2 H_2O$, KHF_2, and boric oxide on optical properties, (4) 124–27.
fluorine substitution for SiO_2 in soda-lime glass, effect, curves, (12) 369–70; chemical analysis and measured properties, (12) 370.
fractional increments, initial, for oxide additions to pure silica glass, (1) 16–17.
freezing method for annealing process, (9) 271; discontinuous freezing method, (9) 273.
frequency distribution and 3-sigma control limits, chart, (12) 385.
furnace assembly diagram for melting-rate tests, effect of grain size of raw materials and cullet additions, (8) 226; see also *Furnaces.*
glass coatings on steel, absence of plastic flow in, studies, (11) 352–54.
homogeneity, measurement of rate, (2) 42.
homogeneity, polariscopic examination of glass sections, (3) 85.
inclusions in, separation method, (5) 139.
lime, silica, daily density, and 3-day density range for ware grade, chart, (12) 381–82.
liquidus temperature, effect of MgO substitution for CaO, curves, (8) 222.
magnesia substitution for CaO in soda-lime glasses, effect on physical properties, (8) 222; effect on liquidus temperature, viscosity, and resistance to distilled water, (8) 222–24.
melting rate, effect of grain size and cullet additions, (8) 225–31.
molten, surface tension, relation to persistence of cords, (5) 143.
Multiform process for high-silica types, (10) 300.
optical, acromatic, description, proportionality, and diagram of calculation, method, (6) 189–91.
anastigmat lenses, design, (6) 194.
"bending" lens, effect on spherical aberration and coma, diagram, (6) 192; effect of cemented surface on astigmatism of lens, (6) 192.
chromatic aberration, proportionality, (6) 190.
collective and dispersive surfaces, (6) 193.
Cooke triplet lens, diagram, (6) 192.
Goerz "Dagor" lens, diagram, (6) 193.
Kodak "Ektar" f/1.5 and Kodak Telephoto Ektar f/3.8, diagrams, (6) 194.
lateral color correction, (6) 190; balancing in lens system, diagram, (6) 191.

Glass, optical (*continued*)
lens, chromatic aberration, calculation of separate elements in, diagram, (6) 191.
lens designer's requirements, (6) 189.
Petzval condition, formula, (6) 193; reducing Petzval sum of photographic objectives, diagrams, (6) 194.
refractive index and dispersive power, definitions, (6) 189; chart, refractive index vs. dispersive power, (6) 191.
refractive index, factors determining choice, (6) 190.
types manufactured in U. S. A., (6) 190.
optical constants, density and refractive index changes, equations for calculation, (1) 10–11.
optical properties, of fluor-crown type, (4) 124–25.
optical properties of Vycor-brand type, (10) 304.
oxide content, effect on surface tension of glass, table, (6) 187.
oxide empirical formulas, oxide and atomic equivalent bases, (2) 35.
phosphorus pentoxide substitution for SiO_2 and $CaO \cdot MgO$ in soda-lime glass, effect and curves, (12) 369–70; chemical analysis and data on properties, (12) 371.
porous, adsorption of N, curve, (10) 300; shrinkage as function of time at varying temperatures, flow of water and acetone through, curves, (10) 301.
porous, properties and process, (10) 299–300.
properties, changes in, effect of composition changes, (1) 10.
Pyrex-brand, fused SiO_2, and Vycor-brand types, physical properties, (10) 301.
Pyrex-brand, vs. Vycor-brand, chemical durability, (10) 303.
refractive index in annealing process, (9) 274.
refractive index change, equations, effect of density and weight, (1) 12; refractive index vs. composition, changes in, table, (1) 12.
refractive index in optical glass, studies, (6) 189.
ring-section examination, measuring apparatus, photo, (3) 88.
sheet, difference in light transmissions through two half fields plotted against analyzer angles, (5) 147.
sheet, light-transmission curves for samples of new and old glass and new glass wet-dried in air blast, (5) 147.
silica in, semimicro-determination method for, (5) 139; silica filtration assembly and tabular data, (5) 141.
sink-float methods for density measurements, (9) 263.
soda-dolomite lime-silica, fluorine and phosphorus pentoxide substitutions in, effect, (12) 369.
soda in, estimation by rapid method, (5) 148.
soda-lime and bottle, stress-optical coefficient, (3) 87.
soda-lime, grain size of raw materials and cullet additions, effect on melting rate, (8) 225–31.
soda-lime, magnesia substitution for CaO, effect on physical properties, (8) 222; effect on liquidus temperature, viscosity, and resistance to distilled water, curves, (8) 222–24.
soda-lime, strontia substitution for CaO, fused viscosity and thermal-expansion curves, (8) 237.
soda-lime-silica, homogenizing rate, centrifuge density-spread method, (2) 42.
soda-lime-silica, surface tensions, calculated, correction for, curve, (6) 187.
soda-lime-silica, thermal expansion, factors for calculations, (9) 262.
soda-silica bottle type, stones in. See *Stones*.
sodium and fluorine substitutions in, chemical analyses and viscosity data, (12) 372.
sodium silicate, change of refractive index with composition, (1) 12.
stones in. See *Glass, cords and stones; Stones*.
stress vs. birefringence, as photoelastic constant or stress-optical coefficient, (3) 87.
stress, permanent, vs. ware quality standards, (3) 88.
stress in, ring-section examination, Babinet compensator for, (3) 85.
stress in, working formulas, (3) 87.
surface tension, calculation, methods, observed-calculated values, (6) 186–88.
surface-tension measurements, spectral in-

Glass, surface-tension measurements (*continued*)
tensity curve of light source and filters, (5) 145; test apparatus, (5) 146.
surface tension, oxide content, effect at 1200° and 1400°C., (6) 187.
thermal history, effect of physical properties, (9) 261.
thermometers. See *Thermometers*.
transformation region, lower limit, (9) 269–70.
viscosity, composition data, maximum and minimum curves, (5) 135–36.
constants for Fulcher equation and viscosity temperature results calculated by least squares method, (5) 136.
measured vs. least squares calculated softening points, (5) 133.
measurements by high-temperature viscometer, (5) 133; by low-temperature viscometer, (5) 135; comparison of results, (5) 135; table of results, (5) 137.
temperature vs. log η data, (5) 137.
-temperature relations for MgO replacements in lime base, (8) 222.
Vycor-brand, properties, (10) 299; physical properties, (10) 301–302; devitrification, chemical durability, operating temperatures, and lampworking properties, (10) 302–303; optical properties, infrared-transmission curves, (10) 304.
ware-quality standards vs. permanent stress, (3) 88.
workability, refined method for control during production, (12) 373.
Glass Container Association, Standard Testing Procedure Committee for Ring-Section Technique, tentative standard for examining and grading glass-container ring sections, (3) 85.
Glasshouse stones. See *Stones*.
Glassy phase in ceramic bodies, quantitative determination, method, (2) 40.
polished sections vs. powder mounts, results compared, (2) 41.
Glazes. See also *Slips*.
aging time and electrolyte additions, curves, (7) 218.
atmosphere control apparatus, diagram, and electrolytic arrangement for constant heating schedule, (6) 166–67.
autoclave test results, (12) 364.
batch formulas for frits in plant tests, (12) 363.
bisque and glazed semivitreous ware, moisture-expansion studies, curves, (12) 355–57.
Bristol, raw lead, and fritted lead borosilicate, chemical composition, test results, curves, data, (7) 211–13.
brown, composition, reflectance measurements and colors fired in various atmospheres, chart and table, (6) 173–74.
clays for, base-exchange capacity vs. coherence value, curve, (7) 219.
coherence-receptivity test method, practical uses, (7) 214.
coherence values and body receptivity, apparatus, photo, (7) 210.
colors in, effect of firing temperature, (6) 165.
consistency, control chart, (7) 216.
for cordierite body, composition and data on glaze fit, (8) 233.
deposition limit and deposition constant, (7) 219–20.
dinnerware, effect of strontia substitutions, (8) 234.
enamels, stains, effect of particle size, (1) 2.
Florida kaolin in, effect of aging and electrolyte addition on consistency, curves, (7) 218; Fla. kaolin and flint, effect on consistency and milling of slip, curves, (7) 218.
flux-block tests of cones 02 to 01 glazes fired at cone 8, photo, (12) 364.
glaze-fit problems, (8) 231–33.
glaze-slip control, detailed studies, (7) 202–203; see also *Slips*.
green, light green, firing atmospheres, chart, (6) 168; reflectance measurements, hue change vs. firing atmospheres, yellowness and lightness data, curves, (6) 169–71; physicochemical nature of changes, (6) 171.
heating schedule, electrolytic arrangement and principle, (6) 167.
impact and chipping test results, (12) 365.
improved technique and apparatus, (7) 209.
leadless and low-lead, molecular formulas and physical properties, (8) 237.
low-temperature, modulus of rupture and glazed-ring tests, data, (12) 364.

Glazes (*continued*)
for low-temperature vitreous ware (cone 01), physical properties, tests, (12) 359.
luster, one-fire, molecular formulas, (2) 63.
luster, "superficial" and hard, (2) 62; acid tests, (2) 64.
milling treatment, curves, (7) 217–18.
for nepheline syenite bodies, body compositions, (12) 359.
oxide composition in cones 01 and 5 glazes, (12) 364.
pink and maroon, compositions and effect of firing atmospheres, (6) 174–75.
plant trials on cone 01 low-temperature glazes, molecular and batch formulas, (12) 363.
pottery, one-fired luster, molecular formulas, (2) 63.
processing and stress developments for low-expansion bodies and durable low-temperature glazes, (8) 231–32.
raw materials, classification of variables, chart of relationships, (7) 215.
receptivity pickup for varying compositions, curves, (7) 220.
standard, and Koenig glaze, formulas, (12) 360; molecular formulas and glaze properties, (12) 361–62.
stresses in, relation to glaze fit, (8) 231; degree of stress, effect of variables, (8) 231–32.
stress variations in initial cooling, curve, (8) 233.
strontia in, molecular formulas and physical properties, tables, (8) 237.
strontia substitutions for PbO, CaO, and ZnO, cone deformation temperatures, (8) 234; fused viscosities, table and photos, (8) 235; thermal-expansion curves, (8) 236.
thermal-shock test results on plant trials, (12) 365.
thickness of application, correlation with air permeability, (7) 207; mechanical dipper for tests, diagram, (7) 208.
triaxial diagrams, glaze properties and molecular formulas for high PbO, MgO, and SrO, and high KNaO, PbO, and BaO-MgO, (12) 360–62.
for vermiculite-containing structural clayware, formula and effect, (2) 51.
wall-tile, glaze and frit formulas, (11) 324; diopside substitutions for feldspar and talc, (11) 326.
water receptivity, coherence values, and thickness, relation, (7) 207–208.
for whiteware body, glaze fit, compositions and data on, (8) 232–33.
yellow, compositions and reflectance measurements in various firing atmospheres, curves and table, (6) 172–73.
Glost kiln refractories, pin chipping, prevention, structure vs. performance, (9) 282–83.
Goerz "Dagor" lens, diagram, (6) 193.
Grain size. See *Particle size*.

High-frequency ceramics, dielectric properties, effect of humidity, (6) 175–81; see also *Dielectrics*.
Homogeneity of glass, soda-lime-silica, centrifuge density spread technique for measurements, (2) 42.
Huggins' factors for calculating glass density, (9) 262.
Humidity, effect on dielectric properties of high-frequency ceramics, (6) 175.
Hunter reflectometer. See *Reflectometers*.
Hydrogen-ion concentration of alcoholic products stored in glass bottles three years, test data and curves, (2) 54; autoclave durability tests, reproducibility, table, (2) 54; data on products studied, (2) 56; correction, (12) 401.
Hydrometer for particle-size tests, photo, (1) 7.
soil, calibration curve, (1) 3.
Hydrometer method. See *Methods*.

Ice point, changes in, effect of long-time aging at constant temperature, (2) 57.
Joule's equation for readings in thermometers, (2) 57.
Illinois clays. See *Clays*.
Impact value, formula for low-temperature vitreous ware tests, (12) 359.
Insulators, body composition, glaze coherence, pickup, and receptivity test data, (7) 211–13.
common solid types, surface resistivities, (6) 179.

Inversion of cristobalite, volume changes in low-to-high inversions, (10) 285.
Iron, enameling, sheet-cleaning test, cleaner strength and available alkali test, (3) 91.
Iron oxide, reactivities in, "sulfate" oxide + lime and "oxalate" oxide + lime, (10) 313.

Joule's equation for drift in ice-point readings of thermometers, (2) 57.
Judd, unit of color difference, definition, (6) 166.

Kaolinite, clean monodispersed fraction, characteristics, correlation between oxygen atoms in kaolinite sheet and in ice, diagram, (3) 80.
migration time vs. particle size, and percentage of clay, curves, (4) 119.
NaOH concentration, effect of migration velocity and zeta potential, curves, (4) 118–19.
particles, effect of charge density and total charge, (4) 120.
particles, forces acting between, calculation, (3) 80.
purified, fractionated particles, cataphoretic velocity, ultramicroscopic method, (4) 116.
Kaolinite suspensions, average diameter and specific surface, (5) 153.
Kaolinite-water suspensions, flow properties, (5) 149; data from modified MacMichael viscosimeter, (5) 159–63.
viscosity vs. volume concentration of solids, relation, (5) 152.
Kaolins. See also *Clays.*
in casting-slip bodies, test methods, (4) 97–111: see also *Slips, casting.*
Florida, aging time and electrolyte additions, effect on glaze consistency, curves, (7) 218.
Florida, dialyzed fraction, relation of pressure to shrinkage, percentage of water, water-film thickness, and repulsive forces between particles, table, (3) 79.
Kilns. See also *Furnaces.*
glost kiln refractories, pin chipping, prevention, (9) 282.
rotary, calcination of topaz ore, (6) 181; diagram, (6) 184.
Kinetics, reaction rates, equation, (10) 310.
Kodak Ektar lenses, diagrams, (6) 194.
Kozeny permeability equation, rate of flow, (11) 319.
Kyanite, kyanite brick. See also *Refractories; Topaz.*
brick with raw topaz, bonding-action temperature, (9) 278.
and kyanite-topaz bodies, volume expansion and porosity, curves, (9) 276.
raw and calcined, raw topaz as high-temperature bond, (9) 275.
-raw topaz bodies, porosity, volume change, and specific gravity, curves, (9) 277.
-topaz bodies, bonding-action temperature, effect on compressive strength, study and curves, (9) 278.
-topaz brick, standard-size, load tests, preparation and curves, (9) 279–80; preheat vs. high-temperature load tests, (9) 281.
-topaz lightweight superduty refractories, (8) 243.
topaz in, raw topaz as bond, chemical analysis and body composition, (9) 275; retention of decomposition products in calcined kyanite, curve, (9) 277–78.

Larnite (α-) and **shannonite** (β-), synthesis, tabular data, (7) 200; reaction tests, (7) 201.
Laws, Fick's law of diffusion, (7) 197.
Stokes', for particle measurement, (1) 3.
Lens. See *Glass, optical.*
Lewis, Squires, and Broughton formula for viscosity measurements, (5) 135.
Lillie formula, aperiodic method for viscosity calculation, (5) 134.
Lime vs. magnesia, separation process, (1) 9.
Lime-chrome mixtures, colors of, calcined in various atmospheres, (6) 168.
Limestone, brucitic, description and processing, (1) 8.
Luster glazes. See *Glazes.*

MacMichael viscosimeter, modified, data on various suspensions, (5) 158–63.
Magnesia, granules, washing and drying process, (1) 9.
Magnesia (*continued*)
vs. limestone, separation process, (1) 9.
in soda-lime glasses as CaO substitute, effect on physical properties, (8) 222; effect on liquidus temperature, viscosity, and resistance to distilled water, curves, (8) 222–24.
Magnesia spinels, reactions with alkaline earth orthosilicates in solid state, (7) 197–202.
Magnesioferrite, synthesis, tabular data, (7) 200; reaction tests, (7) 202.
Magnesium chloride–H_2O, equilibrium system, diagram, (1) 21.
Magnesium chromite, formation from magnesia and ferrous chromite, thermal-decomposition curves, (10) 313.
Magnesium sulfate–H_2O, equilibrium system, diagram, (1) 21.
Manganese dioxide in enamels, effect on metal precipitation at ground coat-iron interface, (11) 350.
Metal stones in flint bottle glass, source, detection, and photomicrographs, (11) 348–49.
Methods, air separator, for steatite-talc particle-size measurements, (11) 320–21; correction, (12) 401.
Andreasen pipette, for particle-size tests, (1) 2; for measurements of steatite talc, (11) 320.
Büchner funnel vs. cup-casting, for tests on clay slips, (4) 111.
Carman, for permeability, (11) 318.
Casagrande hydrometer, for particle-size measurements of steatite talc, (11) 320.
for cleaner solution tests, soap test and free alkali and soluble soap test, (3) 91.
Fresnel's reflection laws, Pfund method, and prism method for determining fire polish on sheet glass, (5) 145.
Fulcher equation for measuring viscosity of glass, (4) 135.
glass, for cordiness and workability control in production, (12) 373.
prism, for determination of fire polish on sheet glass, (5) 145.
semimicro-determination of silica and alumina, (5) 139–40.
sink-float, for density measurements, (9) 263.
soda in, rapid estimation, (5) 148.
tentative standard, of examining and, grading glass-container ring sections, (3) 85.
Harman, for clay-slip permeability, (4) 99.
hydrometer, A.S.T.M. standard method for mechanical analysis of soils cited, (1) 2.
hydrometer, for particle size of talc, (11) 318.
hydrometer vs. pipette, comparison, logarithmic-probability plot, (1) 4.
Kozeny equation of permeability, (11) 319.
Lewis, Squires, and Broughton formula for measurement of viscosity, (5) 135.
Lillie formula, aperiodic method for viscosity calculation, (5) 134.
semimicro-determination of stones and cords in glass, (5) 138.
sieve, vs. sedimentation, for particle-size tests on nonplastics, (1) 3.
soap test and free alkali soluble soap test for cleaner solutions, (3) 91.
temperature gradient, for liquidus temperatures, studies on Na_2O–$CaO \cdot MgO$–PbO–SiO_2 glasses, (3) 81.
Turnbull and Ghering, for measurement of centrifuge density spread in soda-lime-silica glass, (2) 42.
ultramicroscopic, for cataphoretic velocity of purified, fractionated kaolin, (4) 116.
viscosity, least squares calculations of softening points, (5) 133.
Microscopes, polarizing, and quartz wedge for examination of glass-container ring sections, (3) 88–89.
Mill liquors, enamel, soluble salts in, basic physical characteristics, (1) 18–19; pyrochemical behavior, (1) 21–22; effect on film strength and tearing tendency, (1) 25.
Minerals, alkaline earth orthosilicates, optical properties, (7) 199.
clay, and nonclay. See *Clays, clay minerals.*
mineral compounds, synthesis, data, (7) 200.
spinels, simple synthetic types, properties, (7) 199.
Missouri clays. See *Clays.*
Moisture expansion of bisque and glazed semivitreous bodies, curves, (12) 355–57.
of wall-tile bodies with diopside additions fired at different P. C. E., (11) 326.
Müller equation for settling velocity of particles, (3) 77.
Multiform process for high-silica glass. See *Glass.*

Nepheline syenite, particle-size data, (1) 5.
Nepheline syenite bodies, compositions, cone 01 glazes for, (12) 359.
Nepheline stones in glass, source, analysis, photo, (11) 334–35.
Nepheline worm in flint glass, photo and data, (11) 335.
New York diopside for wall tile, (11) 324.
Nickel oxide with Co_3O_4 and MnO_2 in enamels, effect on metal precipitation of ground coat-iron interface, (11) 350–51.

Ohio clays. See *Clays.*
One-fire luster glazes. See *Glazes.*
Optical constants, density and refractive index, changes in, equations for calculation, (1) 10.
Optical glass. See *Glass, optical.*
Optical properties of fluor-crown glass, effect of variations in composition, (4) 121, (4) 124–25.
of orthosilicates, (7) 199.
of Vycor-brand glass, (10) 304.
Orthosilicates, alkaline earth, reactions of magnesia spinels, (7) 197; synthesis of orthosilicates and spinels, (7) 198.
Oxide systems, diagrams, (1) 20–21, (1) 23–24.
Oxides, refractory, suboxide forms, conversion at high temperatures, (10) 293.

Particle size (grain size), Andreasen pipette method, instructions for use, (1) 2; for measurements of steatite talc, (11) 320.
of flint, commercial, (1) 4; of different grades of flint, feldspars, and nepheline syenite, (1) 5.
of flint, effect on ball clay in slips, (4) 108; see also *Slips, casting.*
of flint and feldspar, effect on electrical porcelain, (1) 1; of flint, feldspar, and quartz fractions, previous studies, (1) 1–2.
hydrometer method for measurement, A.S.T.M. procedure, (1) 2.
hydrometer vs. pipette methods, logarithmic-probability plot, (1) 4.
particle shape and differential shrinkage of steatite-talc bodies, (11) 317.
of raw materials and cullet additions to soda-lime glass, effect on melting rate, (8) 225.
of steatite-talc, methods for determination, (11) 320; correction, (12) 401.
suspending media, effect on settling rates, (1) 5–6.
Particles, cataphoretic velocity of purified and fractionated kaolin, ultramicroscopic method, (4) 116.
Periodic tables for systematic classification of dielectric properties, (2) 38.
Permeability, Carman and Kozeny methods, (11) 318–19.
of slip-casting clays, apparatus for tests, (4) 99–100.
Petzval condition in optical lenses, formula, (6) 193; means for reducing Petzval sum of photographic objectives, (6) 194.
Pfund method for determining apparent Brewsterian angle vs. angle calculated from index of refraction of glass, (5) 145.
Phase diagrams. See *Equilibrium diagrams; Equilibrium systems.*
Phosphorus pentoxide as substitute for SiO_2 and $CaO \cdot MgO$ in soda-lime glass, effect and curves, (12) 369–70; chemical analysis and measured properties, (12) 371.
Picrochromite, synthesis, tabular data, reaction test, (7) 200–201.
Pin chipping. See *Saggers.*
Pipette method for particle size. See *Methods, Andreasen pipette.*
Pittsburgh Plate Glass Co., optical glass types and characteristics, (6) 190.
Plastic clays, water film in, nature of, (3) 77.
Plastic flow in glass coatings on steel, tests on absence of flow, (11) 352.
Polarizing microscope for examination of glass-container ring sections, photo and method, (3) 88–89.
Porcelain, body composition, glaze coherence, and receptivity test data, (7) 211–13.
electrical, feldspar in, injurious effects on dielectric properties cited, (2) 33.

Porcelain (*continued*)
electrical, flint and feldspar in, effect of particle-size variations, (1) 1.
high-frequency, effect of humidity on dielectric properties, (6) 175.
vs. steatite, dissipation factor vs. temperature, curves, (6) 176.
Porcelain Enamel Institute, acid-resistance test, method, (12) 367.
Porous glass. See *Glass, porous.*
Pottery, glazed, one-fire luster, practical production and decorative techniques, (2) 62–64.
Prism method for determining fire polish on sheet glass, (5) 145.
Pyrex-brand glass. See *Glass, Pyrex-brand.*
Pyrometric cone equivalent of silica fire clay, effect of clay quality and fineness of grind, (8) 239–40.
Pyrophyllite-talc bodies, moisture-expansion data at various exposure conditions, tables, (12) 356.

Quartz, grain size, effect on body contraction and expansion, previous work cited, (1) 1–2.
preheating of, effect on reactivity, preheating in O_2, SO_2, air, and SO_3, curves, (10) 313.
as source of stones in bottle glass, (11) 342.

Rankin and Merwin diagram, $MgO–Al_2O_3$, cited, (11) 327; curve, (11) 329.
Reactions, Ag_2HgI_4, mechanism of formation, diagram, (10) 311.
chemical, bibliography, (1) 23–24.
chemical potential of diffusing particles during, (10) 309.
kinetic treatment for reaction rate, (10) 310.
rates, topochemical factors in, influence, (10) 311–12.
reaction constants, diagram and equation, (1) 14–15.
reaction mixtures, increased adsorption, curves, (10) 315.
reaction products, fresh, expanded lattice data, (10) 311.
simple additive, course of, period of primary reaction, (10) 314.
between solid salts, topochemical factors, (10) 308.
in solid state, rate-determining factors, (10) 308.
Receptivity data for slip glazes. See *Glazes; Slips.*
Reflectance, measurements of green, yellow, and brown glazes, effect of various firing atmospheres, (6) 170, (6) 172, (6) 174.
Reflectometer, Hunter, for color measurement of glazed surfaces, use, (6) 168.
Refraction, refraction constants and specific refraction constants, diagrams and equations, (1) 14–15.
Refractive index of glass, calculation of changes in, equations, (1) 11; vs. composition changes, table, (1) 12.
Refractories, brucite magnesia for, source, processing, and uses, (1) 8–10.
clays for. See *Clays.*
fusion-cast, with high-chrome ore content, tests, (11) 327.
fusion experiments in system $MgO–FeO–Cr_2O_3–Al_2O_3$, (11) 327.
glost kiln, pin chipping, cause and prevention, linear expansion curves, (9) 283–84.
high-grade mullite-type, topaz ore as substitute for India kyanite, (6) 181.
Illinois plants, thermal analyses of fire clays, curves, (3) 74–75.
kyanite-topaz brick, load-test results, (9) 281; see also *Kyanite.*
kyanite-topaz, lightweight compositions, effect of plastic kaolin additions, properties before and after reheat tests, (8) 242; see also *Refractories, lightweight.*
kyanite-topaz, properties after preheat at 1500°C., variable temperature load-test results, (9) 280.
lightweight, superduty, Bur. Mines vs. commercial test samples, reheat test properties at 1600°C., (8) 244; load tests, constant and variable, tables, (8) 245.
lightweight, superduty, porosity and density curves, (8) 243; composition and reheat test results, tables, (8) 244.
load tests for kyanite-topaz brick, (9) 279–81.
pyrometric cone equivalent (P.C.E.), effect of clay content and quality, (8) 240.
in Owens revolving pot, drips and stalactites, photo, (11) 331.
Refractories (*continued*)
refractory origin of stones in glass, (11) 334.
refractory oxides, suboxide forms, conversion at high temperatures, (10) 293; significance in study of refractories and slags, (10) 297.
silica brick, mineral analysis and volume expansion of cristobalite, (10) 285.
silica fire clay, chemical analysis of raw materials, effect of fineness of grind on P.C.E., tables, (8) 239–40.
and slags, suboxide forms, significance, (10) 297.
topaz, domestic kyanite, and synthetic mullite corundum as substitution for India kyanite, raw topaz as high-temperature bond for domestic kyanite, IV, (9) 275.
topaz ore, calcination in rotary kiln, (6) 181; see also *Topaz.*
zirconium, in glass furnaces as source of stones, (11) 338.
Refractory stones in glass. See *Stones.*
Ring sections of glass containers, tentative standard procedure for examination, (3) 86.
Rotary kilns. See *Kilns.*
Rutile bodies, compacting pressure vs. dimensions, dielectric constant, and dissipation factor, tables, (6) 178.
dielectric constant and temperature dependence, curve, (6) 179.
dissipation factor and dielectric constant vs. temperature, (6) 176; variation of dissipation factor and capacitance with temperature, curves, (6) 176.

Saggers, pin chipping, prevention, (9) 282; structure vs. performance, relation, (9) 283; refractory bases, expansion curves, (9) 283–84.
Sanitary ware, body compositions, glaze coherence, pickup, and receptivity test data, (7) 211–13.
Sedimentation, analyses, effect of nonpolar liquids, (1) 7.
methods for particle-size measurements of steatite talcs, (11) 321; correction, (12) 401.
Semivitreous ware. See *Vitreous ware, semivitreous.*
Shales from northern and southern Ill., thermal curves, (3) 74–75; see also *Clays; Kaolins.*
Shrinkage, differential, and particle shape of steatite talc bodies, (11) 317.
Sieve method. See *Methods.*
Silica and alumina in glass, semimicro-determination methods, (5) 139–40.
conversion to silicon monoxide at high temperatures, SiO history, (10) 293–94; properties, uses, and experiments on SiO, (10) 294–95.
in enamels, effect on abrasion resistance, (12) 367–68.
expansion data, properties of test samples, inversion data, (10) 290–91.
inversions, sluggish and low-to-high types, (10) 285.
suboxide forms, CrO, properties and functions, (10) 296.
Silica brick. See *Refractories.*
Silica fire clay, pyrometric cone equivalent, effect of clay fineness of grind and quality, (8) 239–40.
Silicon monoxide, vitreous, decomposition products, photomicrograph, (10) 294; powdery sublimate of SiO, photo, (10) 294.
Sink-float methods for glass density measurements, (9) 263.
Slips, casting, aging time for, effect on kaolin and ball clays, curves, (4) 105.
casting, amount and temperature, effect on kaolin, curves and data, (4) 104.
casting-rate determination, cup method, (4) 112.
clay-flint ratio, effect on kaolin and feldspar substitution for flint, (4) 107.
control methods, (4) 103.
mixing time, mixing sequence, and variation of vacuum pressure, effect, curves and table, (4) 106.
particle numbers and spacing in suspension, calculation, (5) 157.
plaster of Paris mold for, design, (4) 102; mold for cup-casting rate determination, (4) 102.
viscosity curves, actual vs. calculated, viscosity values, (5) 156–57; viscosity and yield-point calculations, (5) 157.
water content, effect, curves, (4) 103.
clay, cup method for casting rate, (4) 112.
Slips (*continued*)
clays for, casting characteristics, improved methods, (4) 97.
coherence test apparatus, diagram, process, (7) 204.
drier and stirrer for preparation, (4) 99.
electrolytes in, effect on kaolin and ball clay content, curves, (4) 107–108, (4) 110.
enamel, clays for, physical and chemical properties, X-ray patterns, (9) 253–254.
enamel, clays in, single clays and in combination, properties, (9) 258–60.
flint in, effect of particle size on ball clays, curves and data, (4) 108.
glaze, coherence, surface tension, thickness, and firing, test results, (7) 204–207; see also *Glazes.*
glaze, specifications, flow-stress curve, (7) 203.
properties, Büchner funnel vs. cup-casting tests, thixotropy and shrinkage data, (4) 109; properties of bodies and tests compared, (4) 111.
surface-tension apparatus, and tests, (7) 204–205.
thixotropy tests, Stormer viscosimeter for, (4) 99; test curves on casting slips, (4) 109.
viscosity, apparent, at different rates of shear, curves, (5) 152.
Smoluchowski formula for particle concentration, (4) 117.
Soda in glasses, rapid method for estimating, (5) 148.
Soda-dolomite lime-silica glasses, fluorine and phosphorus pentoxide substitutions in, effect, (12) 369.
Sodium borate–H_2O, equilibrium system, diagrams, (1) 20.
Sodium carbonate–H_2O, equilibrium system, diagram, (1) 20; $NaCO_3$–NaF, diagram, (1) 22; $NaCO_3$–NaOH, diagram, (1) 23.
Sodium fluoride–H_2O, equilibrium system, diagram, (1) 20; NaF–$NaSO_4$, diagram, (1) 22.
Sodium hydroxide in cleaner solutions, formulas for calculation, (3) 93.
–H_2O, equilibrium system, diagram, (1) 21.
Sodium nitrite–H_2O, equilibrium system, diagram, (1) 21.
Sodium pyrophosphate–H_2O, equilibrium system, diagram, (1) 20.
Sodium sulfate–H_2O, equilibrium system, diagram, (1) 21; Na_2SO_4–$MgSO_4$ and Na_2SO_4–Na_2CO_3, diagrams, (1) 23.
Soil hydrometer, calibration curve, (1) 3.
Solids in topochemical states, source, (10) 312.
Solid state, alkaline earth orthosilicates, reactions of simple magnesia spinels with, (7) 197–202.
reaction rates between solid salts, effect of topochemical factors, (10) 308.
Solubility test for enameled cooking ware. See *Cooking ware.*
Soluble salts in enamel mill liquors, effect on enamel film strength and tearing tendency, (1) 25; specific types, effect on tearing of enamels, (1) 30.
in enamel mill liquors, fundamental properties, (1) 17; basic physical characteristics, tables, (1) 18–19; pyrochemical behavior, (1) 21; possible chemical reactions, formulas, (1) 22.
ionization behavior, reactions between, effect on clay–water systems, (1) 20.
Sound-absorption, tests on plastic-process tile with vermiculite, (2) 51.
Specific shape factor, calculation, (11) 317–18.
Specific surface, equation for calculation, (1) 4.
Spinel, formation, schematic mechanism, (10) 314.
and orthosilicates, synthesis of, (7) 198.
synthesis, tables and reaction tests, (7) 200–201.
synthetic, properties, (7) 199.
Steatite, Bakelite, and mica, variation of dissipation factor with frequency, curves, (6) 177.
definition and formula, (2) 33.
dissipation factor vs. maximum firing temperature, curve, (6) 179.
vs. porcelain, dissipation factor vs. temperature, curves, (6) 176.
and rutile materials, variation of dissipation factor with frequency, curves, (6) 177.
surface resistivity vs. air pressure for varying relative humidity, (6) 180.
Steatite bodies with talc and various powdered glasses, (2) 34; empirical formulas of glasses, (2) 35.

Steatite dielectrics, absorption measurements and electrical tests, (2) 35–36; furnace for measurements, diagram, (2) 36.
crystalline and glassy phases, (2) 33.
electrical properties, definitions and formulas, (2) 34; tabular data, (2) 37.
periodic table for systematic classification, (2) 38.
Steatite-talc, air-separator method for particle-size measurements, disadvantages, (11) 320–21; correction, (12) 401.
bodies, particle shape and differential shrinkage, correlation, (11) 317.
particle-size distribution, (11) 320.
Steel, glass coatings on, absence of plastic flow in, studies, (11) 352–54.
Stokes' law for particle measurement, (1) 3.
Stones. See also *Glass, cords and stones.*
batch, source, prevention, photomicrographs, (11) 338–40.
in bottle glass, quartz as source, (11) 342.
clay, chemical analysis, source, and photos, (11) 335–36.
cullet as source, flint samples, photo and discussion, (11) 331, (11) 333.
devitrification types, identification, (11) 330; in bottle glass, source, cause, photomicrographs, (11) 340–42.
devitrite and cristobalite as source in bottle glass, description and photomicrographs, (11) 346–47.
diopside as source in bottle glass, (11) 345–46.
in flint bottle glass, (11) 347–49.
in flint cullet, source, photo, (11) 331.
in flint glass, nepheline worm, photos and data, (11) 335.
from furnace refractories, origin and source, (11) 333–34.
in glass, bibliography and footnote citations, (11) 330–50.
in glass, opaque vs. translucent, differentiation, (11) 330.
glasshouse, in flint, amber and green bottle glass, source, identification, and elimination, (11) 330–50.
glasshouse, in melting soda-lime bottle glass, types, description, and source, photomicrographs, (11) 330.
metal types in flint bottle glass, detection and photomicrographs, (11) 348–49.
in molten cast refractory, description and photomicrograph, (11) 336–37.
nepheline type, photos, sources, and chemical analysis, (11) 334–35.
silica refractory, chemical analysis, source, photomicrographs, (11) 338.
special refractory, effect of zirconium, (11) 338.
sulfate in flint bottle glass, source and photomicrographs, (11) 347–48.
tridymite and cristobalite as source in bottle glass, (11) 343.
wollastonite as source in bottle glass, description and photomicrographs, (11) 344–45.
Stormer viscosimeter for permeability tests on casting clays, (4) 99–100; thixotropy test curves, (4) 109.
Stress in glass and glazes. See *Glass; Glazes.*
Strontia in dinnerware glazes as PbO, CaO, and ZnO replacement, (8) 234.
Strontium, calcium, and barium compounds, properties and eutectic melting temperatures, (8) 234.
Strontium orthosilicate, synthesis, tabular data, reaction tests, (7) 200–201.
Structural materials, vermiculite as raw material for, (2) 50.
Suboxide forms of refractory oxides. See *Refractories, refractory oxides.*
Sulfate stones in flint bottle glass, source and photomicrographs, (11) 347–48.
Surface tension of glaze slips, curves for Tenn. ball clay and Texas clay, (7) 296.
Suspensions, kaolinite-water, flow properties, (5) 149; flow properties of suspended spheres, Einstein, Hatschek, and Arrhenius laws for, (5) 151.
particles in, at varying concentrations, (5) 156.
Synthesis of spinels and orthosilicates, (7) 198; of compounds, table, (7) 200.
Systems, clay–water, effect of various soluble salts, (1) 20.
MgO–Al_2O_3, Rankin and Merwin diagram cited, (11) 327; curve, (11) 329.
MgO–FeO–Cr_2O_3–Al_2O_3, fusion experiments in, (11) 327.

Talc-clay body, shrinkage curves, effect of particle size, (11) 322.
commercial, particle-size, comparisons, (11) 321.
and feldspar, diopside substitution in wall-tile body, (11) 324.
Manchurian, for steatite dielectrics, chemical analysis, (2) 35.
materials, particle type, specific surface, and volume data, (11) 319.
particle size, hyrometer method for determination, (11) 318.
-pyrophyllite bodies, moisture-expansion data at various exposure conditions, tables, (12) 356.
sedimentation methods for measurements on particle size, (11) 321.
shrinkage control, effect of particle shape and blends, (11) 317.
specific shape factor and shrinkage, statistical data, (11) 319.
standard and fine grinds, particle-size distribution curves, (11) 322; shrinkage curves, (11) 323.
Tearing of enamels. See *Enamels.*
Telescope design, (6) 191.
Thermal analysis, differential, application to prospecting, (3) 74–75.
differential, of clays and shales, control and prospecting method, (3) 65.
differential, of common clay-minerals and nonclay minerals in clays and shales, (3) 68; of prepared mixtures of clay and nonclay minerals, (3) 69; thermal curves for synthetic clay mixtures, (3) 70.
Thermal decomposition, effect on reactivity in magnesium formation, (10) 313.
Thermal expansion. See *Expansion.*
Thermometers for density changes in glass, (2) 61.
drift in ice-point readings, reversals and complex effects, (2) 60.
glass, ice point, effect of aging, (2) 57; ice-point change vs. time, curves, (2) 59.
Thixotropy, definition, equation for thixotropy of suspension, (5) 154; curves for thixotropy of H-kaolinite fractions, (5) 154.
method of determination, diagram, (5) 150.
tests on clays for casting slips, Stormer viscosimeter for, (4) 99; test curves, (4) 109.
Tin-chrome system, colors developed, (6) 174.
Topaz, calcination in rotary kilns, data for, (6) 182.
calcined and raw, screen analyses, physical properties, (6) 183; chemical analyses, raw materials, products, (6) 182; dust and volatilization losses, (6) 185.
in kyanite bodies. See also *Kyanite.*

Topaz (*continued*)
raw, as high-temperature bond for raw and calcined kyanite, (9) 275.
Topochemical factors, significance on rate of reactions between solid salts, (10) 308.
Tridymite and cristobalite as source of stones in bottle glass, (11) 343.
Turnbull and Ghering method, for measurement of centrifuge density spread in soda-lime-silica glass, (2) 42.

Vermiculite, expanded, for structural clayware, uses, and tests, (2) 50.
in structural clayware, thermal-conductivity and sound-absorption tests, (2) 51.
Viscometers, high-temperature, concentric cylinder, methods of use, photos, (5) 130–31.
low-temperature, method of use, photo, (5) 132–33.
MacMichael, modified, data on various suspensions, (5) 158–63.
Stormer, for thixotropy tests on clays, (4) 99; test curves, (4) 109.
Viscosity of container glass, (5) 129; high- and low-temperature viscometers for measurements, photos, (5) 130–32; maximum and minimum viscosity curves, diagram of high-temperature viscosity furnace, (5) 136.
high-temperature measurements, methods of calculation, (5) 133–34.
of suspension, relation to concentration of solid, formula for, (5) 152.
Vitreous ware. See also *Chinaware; Dinnerware.*
low-temperature, cone 01 glazes, (12) 358.
semivitreous, clay-flint-feldspar body, moisture-expansion data, (12) 357.
semivitreous, moisture-expansion data, on bisque and glazed bodies, (12) 355; observed and ultimate expansion at cone 9, curve, (12) 357.
Volume-expansion measurements on cristobalite. See *Expansion.*
Vycor-brand glasses. See *Glass, Vycor-brand.*

Wall tile, colors in, effect of diopside substitutions for talc and feldspar, (11) 325.
diopside additions and substitutions for talc and feldspar, compositions, firing temperatures, thermal-expansion, glaze trial results, moisture-expansion, and absorption data, (11) 324–36.
glaze and frit formulas, glaze trials, test results, (11) 324, (11) 326.
Water film in plastic clay, nature, determination, and stability, (3) 77–79.
Whiteware. See also *Chinaware; Porcelain, electrical; Vitreous ware.*
glassy bond in, quantitative determination, method, (2) 40.
glazes. See *Glazes; Slips.*
petrographic study of polished sections and powder mounts, for glassy phase, crystals, and pores, (2) 40–41.
semivitreous bodies, moisture-expansion data at varying storage periods, (12) 355–57.
Wollastonite as source of stones in bottle glass, photomicrographs, (11) 344–45.

Zinc-aluminum-spinel, formation, photo, (10) 309.
-iron-spinel formation, intermediate stages in, diagram, (10) 314.
Zinc oxide and α-iron oxide, lattice imperfections, tabular data, (10) 312.

FOOTNOTE CITATIONS INDEX TO THE JOURNAL
Volume 27, 1944

The reference number in parentheses refers to the *monthly* issue of the *Journal;* the number following is the *page* number.

Abramson, H. A., determination of electrical charge of surfaces by microscope method of electrophoresis, (4) 116.
Adams, L. H., and Williamson, E. D., annealing of glass, (2) 58, (5) 146, (9) 272.
Albers-Schönberg, E., Hochfrequenzkeramik (high-frequency ceramic products), (6) 176.
Albro, A. B., analysis of silicon compounds, (10) 293.
American Institute of Electrical Engineers, American standard definitions of electrical terms, (6) 180.
American Society of Heating and Ventilating Engineers, Guide on thermal conductivity of materials, (2) 51.
American Society for Testing Materials, Nonmetallic materials, III, 1942, (6) 180; standard method of mechanical analysis of soils, A.S.T.M. designation D422–39, (1) 2; Symposium on new met hod particle-size determination in subsieve range, (1) 2; tentative method of hydrostatic pressure test on glass containers, C147–40T, (3) 86; tentative method of polariscopic examination of glass containers, C148–40T, (3) 85; tentative method of thermal-shock test on containers, C149–40T, (3) 85.
American Standards Association, control-

chart method of controlling quality during production, (12) 374.
Andreasen, A. H. M., grinding of materials, theoretical and experimental research on particle-size determinations incident to disintegration process, (1) 2; validity of Stokes' law for nonspherical particles, (1) 4.
Andrews, A. I., Enamels, (1) 23, (2) 46, (3) 90, (11) 354.
Andrews, A. I., and **Cook, R. L.**, Enamel laboratory manual, (2) 48.
Andrews, A. I., and **Swift, H. R.**, iron oxide in enamel glass as dissolved from metal base, (2) 46.
Andrews, A. I., and **Zwermann, C. H.**, fundamentals of colors in porcelain enamels, (6) 173.
Annual Tables of Constants and Numerical Data, Vol. IV, (1) 23.
Arrhenius, Svante, Innere Reibung verdünnter wässeriger Lösungen, (5) 151.
Athavale, V. T., and **Jatkar, S. K. K.**, reactions of chromates at high temperatures, decomposition of calcium chromate, III, (6) 169.
Austin, J. B., methods of representing distribution of particle size, (1) 4.

Babcock, C. L., surface-tension measurements on molten glass by modified dipping-cylinder method, (6) 186; viscosity and electrical conductivity of molten glasses, (5) 134.
Bacon, F. R., and **Burch, O. G.**, effect of time and temperature on accelerated chemical durability tests on commercial glass bottles, (2) 53.
Badger, A. E., effect of various gaseous atmospheres on vitrification of ceramic bodies, (10) 297.
Badger, A. E., **Parmelee, C. W.**, and **Williams, A. E.**, surface tension of various molten glasses, (6) 186.
Badger, A. E., and **Pinnow, H. R.**, vanadium and chromium oxides in refractories as aids in elimination of cords in glass, (5) 143.
Badger, A. E., **Uhrmann, C. J.**, and **Ottoson, A. C.**, use of lead oxide in glassmaking refractories, (5) 143.
Balinkin, I. A., color symposium, measurement and designation of small color differences, V, (6) 166.
Baly, E. C. C., Spectroscopy, (4) 121.
Barr, Guy, Monograph of viscometry, (5) 164.
Barrer, R. M., diffusion in and through solids, (7) 197.
Barth, T. F. W., cristobalite structures: high cristobalite, I, (10) 286; low cristobalite, II, (10) 286.
Baumann, H. N., Jr., X-ray diffraction examination of material having composition SiO, (10) 294.
Baver, T. D., Soil physics, (1) 5.
Bazilevich, A., synthesis of spinels, (7) 198.
Beam, J. R., effect of opacifiers on fused viscosity of feldspathic glazes, (8) 234.
Bell, W. C., evaluation of glaze-fit test methods, (8) 236.
Bellière, Marcel, crystallization of pseudowollastonite by devitrification of glasses, (11) 330; formation of cristobalite as octahedra in devitrified glass, (11) 350.
Bénard, J., and **Chaudron, Georges**, preparation of ferrites by substitution for ferrous irons in magnetite, (7) 198.
Benner, R. C., **Baumann, H. N., Jr.**, and **Easter, G. J.**, refractory and abrasive material and process of making, (11) 327.
Bennett, A. L., special depth gauge for measurement and control of ceramic coatings, (7) 203.
Bennett, H. F., telephoto objective, (6) 194.
Berberich, L. J., and **Bell, M. E.**, dielectric properties of rutile form of TiO_2, (6) 176.
Berenz, H., and **Gingold, J.**, insulator, (2) 34.
Berger, E., and **Freundel, O.**, oxide compositions of fluor-crown glasses, (4) 121.
Bernard, Jacques, Etude de la Decomposition du Protoxide de Fer et de ses Solutions Solides, (11) 350.
Bhatanger, S. S., **Cameron, A.**, **Harbard, E. H.**, **Kapur, P. L.**, **King, A.**, and **Prakash, Brahm**, magnetic susceptibilities of metallic oxides with special reference to those of chromium and manganese, (6) 169.
Biltz, W., and **Ehrlich, P.**, volatilization of silicon as lower oxide, (10) 294.
Blair, G. W. S., measurements of plasticity of clays, (7) 202.
Blair, T., certain accessory products of blast furnaces, (10) 298.
Blanc, L., and **Chaudron, G.**, transformations and oxidation of sesquioxides of chromium, (6) 169.
Bleininger, A. V., and **Hornung, M. R.**, notes on casting, (4) 98.
Bleininger, A. V., and **Riddle, F. H.**, special spark-plug porcelains, (2) 33.
Bock, F., several innovations in technical utilization of silica, (10) 293.
Boericke, F. S., equilibria in reduction of chromic oxide by carbon and their relation to decarburization of chromium and ferrochrome, (10) 296.
Bonhoeffer, K. F., existence of gaseous silicon monoxide, (10) 294.
Bonthron, K. J. A., and **Durrer, Robert**, studies for determination of melting diagrams of system Al_2O_3–Cr_2O_3–MgO, (7) 199.
Boonton Radio Corp., Instructions and manual of radio frequency measurements, (2) 34.
Bouyoucos, G. J., comparison between pipette method and hydrometer method for mechanical analyses of soil, (1) 2; hydrometer as new and rapid method for determining colloidal content of soils, (1) 2; sensitive hydrometer for determining small amounts of clay or colloids in soils, (1) 2.
Bowen, N. L., identification of stones in glass, (11) 330.
Bowen, N. L., and **Greig, J. W.**, system Al_2O_3–SiO_2, (11) 350.
Bradley, R. S., **Schroeder, F. W.**, and **Keller, W. D.**, study of refractory properties of topaz, (6) 181, (9) 278.
Bragg, W. L., Atomic structures of minerals, (10) 285.
Brauer, G., oxides of columbium, (10) 297.
Brunauer, S., **Emmett, P. H.**, and **Teller, E.**, adsorption of gases in multimolecular layers, (10) 300.
Bryant, E. E., controlled boiling acid test for porcelain enamels, (4) 113.
Büssem, W., **Schusterius, Carl**, and **Stuckhardt, Karl**, constitution of steatite, glass phase, II, (2) 33.

Cameron, A., **Harbard, E. H.**, and **King, A.**, nonstoichiometric oxides, oxides of chromium, I, (6) 169.
Canfield, J. J., copperheading in enamel, causes and methods of prevention, (2) 46.
Carman, P. C., determination of specific surface of powders, I, (11) 318; shape and surface of fine powders by permeability method, (1) 2.
Carter, W. K., and **King, R. M.**, sodium aluminate as an electrolyte for casting-slip control, (4) 98.
Chesters, J. H., all-basic open hearth, II, (7) 202.
Chesters, J. H., and **Parmelee, C. W.**, measurement of reaction rates at high temperatures, (7) 198.
Clark, G. L., **Ally, Abde**, and **Badger, A. E.**, lattice dimensions of spinels, (7) 199.
Clark, G. L., **Howe, E. E.**, and **Badger, A. E.**, lattice dimensions of solid solutions in the system MgO–Al_2O_3, (7) 199.
Cohn, W. M., problem of heat economy in ceramic industry, II, (10) 286.
Cole, S. S., effect of size of grain on properties of silica cement, (8) 241; variations in P.C.E. of silica cements and fire clays, (8) 241.
Cole, S. S., **Scholes, S. R.**, and **Amberg, C. R.**, correction in specific gravity and unit cell size of $Na_2O \cdot B_2O_3$, (1) 23.
Comey, A. M., and **Hahn, D. A.**, Dictionary of chemical solubilities, (1) 23.
Conrady, A. E., microscopic optics in Dictionary of applied physics, Vol. IV, (6) 190.
Cook, H. L., note on solubility of enamel frit in mill water, (1) 25; observations on effect of various electrolytes added to enamel suspensions made with and without clay, (1) 25.
Cooke, R. D., effect of furnace atmosphere on firing of enamel, (6) 165; study of soluble salts in enamels, (1) 25.
Cosgrove, J. M., spot test as aid in rapid evaluation of cleaners, (3) 90.

Danielson, R. R., effect of soluble salts on properties of enamels, (1) 25.
Davis, H. E., and **Lueders, R. L.**, simplification of ring method for determining glaze stresses, (12) 355.
Debye, P., and **Hückel, E.**, Bemerkungen zu einem Satze über Kataphoretische Wanderungsgeschwindigkeit suspentierter Teilchen, (4) 117.
Dickinson, H. C., heat-treatment of high-temperature mercurial thermometers, (2) 57.
Dieckmann, T., and **Hanf, O.**, notice on chromous oxide, (10) 296.
Dietzel, A., methods for investigation of little stones and knobs in glass, (11) 350; practical importance and calculation of surface tension in glasses, glazes, and enamels, (6) 186.
Dilaktorskii, N. L., synthesis of some minerals of the spinel group, (7) 198.
Dodd, A. E., action of water vapour on silica brick at high temperatures and possible industrial significance, (10) 297.
Drude, P., Theory of optics, (5) 145.

Earhart, W. H., use of N. C. kaolin in casting bodies, (4) 98; use of washed N. C. kaolin as ingredient in porcelain bodies, (4) 98.
Ebelman, M., cited on method of spinel synthesis, (7) 198.
Einstein, A., Neue Bestimmung der Moleküldimensionen, (5) 151.
Eirich, F., **Bunzl, M.**, and **Margaretha, H.**, Viskosität Suspensionen und Lösungen, Kugelsuspensionen (viscosity of globular suspensions), IV, (5) 151.
Eirich, F., **Margaretha, H.**, and **Bunzl, M.**, Viskosität von Suspensionen, Viskosität von Stäbchensuspensionen (viscosity of acicular suspensions), VI, (5) 152.
Eitel, W., flow currents in automatic glassworking in Owens process, special current configuration in finished bottles, (3) 86; flowing processes in automatic manufacture of bottles by feeder process with Owens Bottle Company machine, (3) 86; processes of flow in automatic working of glass in Owens process, (3) 86; studies of flow conditions in automatic glassworking by feeder-fed (Lynch process) machines, (3) 86.
Ellis, R., Eigenschaften der Olemulsionen und electrische Ladung, (4) 116.
Emmett, P. H., measurement of surface areas of finely divided or porous solids by low-temperature adsorption isotherms, (10) 299; new method for measuring surface areas of finely divided materials and for determining size of particles, (1) 2.
Emmett, P. H., and **DeWitt, T. W.**, low-temperature adsorption of nitrogen, oxygen, argon, hydrogen, *n*-butane and carbon dioxide, (10) 300.
Endell, Kurd, and **Rieke, R.**, transformation of silicic anhydride at high temperatures, (10) 286.
English, S., and **Turner, W. E. S.**, heat expansion of soda-lime glasses, (2) 62.
Ewald, P. P., and **Hermann, C.**, Strukturbericht, 1913–1928, (10) 286.
Ewing, W. W., specific surface of pigments by adsorption from solution, (1) 2.

Fang, S.-M., crystal structure of sodium metaborate, $NaBO_2$, (1) 24.
Feild, A. L., method for measuring viscosity of blast-furnace slag at high temperature, (5) 130.
Fenner, C. N., relations between tridymite and cristobalite, (11) 350; stability relations of silica minerals, (10) 286.
Ferguson, W. F. C., chromium oxide and vanadium oxide band spectra, (10) 296.
Ferry, J. D., and **Parks, G. S.**, viscous properties of polyisobutylene, (5) 134.
Fisk, H. G., and **McCaughey, W. J.**, equilibrium studies in systems containing magnesium oxide, iron oxide, and magnesium aluminate, (7) 199.
Flusin, R., silicon monoxide and oxycarbides, "Monox" and "Fibrox," (10) 293.
Frame, W. M., Casing settling depths not assured by physical properties of steel, (11) 353.
Freundlich, H., and **Jones, A. D.**, sedimentation, volume, dilatency, thixotropic, and plastic properties of concentrated suspensions, (5) 151.
Freundlich, H., and **Röder, H. L.**, dilatency and its relation to thixotropy, (5) 151.
Fricke, R., and **Ackermann, P.**, heat content and lattice structure of active ferric oxide, (10) 312; thermal and X-ray characterization of irregular lattice distortions in zinc oxide, (10) 312.
Fricke, R., and **Dürr, W.**, active substances, thermochemical and X-ray investigation

of reactions during formation of zinc-iron spinel from active zinc oxide and various kinds of ferric oxide, XXXVII, (10) 314.
Fricke, R., and Gwinner, E., quantitative interpretation of irregular lattice distortions and impurities of amorphous material in active substances, (10) 312.
Fritz, E. H., and Donnenwirth, A. L., observations in casting of heavy electrical porcelains, (4) 97.
Fulcher, G. S., analysis of recent measurements of viscosity of glasses, (5) 133.

Geller, R. F., and Creamer, A. S., moisture expansion of ceramic whiteware, (12) 355; note on moisture expansion of ceramic whiteware in storage and in service, (12) 355.
Geller, R. F., Evans, D. N., and Creamer, A. S., effects of particle size of a potter's flint and feldspar in whiteware, (1) 1.
Getman, F. H., Outlines of theoretical chemistry, (12) 358.
Ghering, L. G., and Knight, M. A., properties and diagnosis of cords in pressed and blown glassware, (12) 374.
Ghosh, C., band spectrum of chromium oxide, (10) 296.
Gifford, J. W., quartz-fluorite for achromatic lens, (4) 121.
Glass Container Association of America, polariscopic examination of glass container sections, (9) 265.
Glazebrook, R., Dictionary of applied physics, Vol. IV, (6) 190.
Goodeve, C. F., and Whitfield, G. W., measurement of thixotropy in absolute units, (5) 150.
Gottfried, C., and Shossberger, F., Strukturbericht, Vol. III, 1933–1934, (10) 286.
Goucher, F. S., and Ward, H., problem in viscosity, thickness of liquid films found on solid surfaces under dynamic conditions, (7) 203.
Goudge, M. F., preliminary report on brucite deposits in Ontario and Quebec and their commercial possibilities, (1) 8.
Granat, I. Y., reduction of chromium oxide, (10) 296.
Greig, J. W., formation of mullite from cyanite, andalusite, and sillimanite, (6) 181.
Greig, J. W., Posnjak, E., Merwin, H. E., and Sosman, R. B., equilibrium relationships of Fe_3O_4, Fe_2O_3, and oxygen, (6) 173.
Griffin, R. C., Technical methods of analysis, 2d ed., (10) 305.
Grim, R. E., modern concepts of clay materials, (3) 65; relation of composition to properties of clay, (3) 65.
Grim, R. E., and Bradley, W. F., investigation of effect of heat on clay minerals, illite and montmorillonite, (3) 68, (9) 253.
Grim, R. E., and Rowland, R. A., differential thermal analyses of clay minerals and other hydrous materials, (3) 68.
Grunewald, M. E., systems CaO–Fe_2O_3 and MgO–Fe_2O_3, (7) 199.

Haessler, C. G., solubility of ferric oxide in porcelain enamel ground coats, (2) 46.
Hainbach, R., Pottery decorating, (2) 62.
Hall, F. P., casting of clayware, a résumé, (4) 97; methods of measuring plasticity of clays, (4) 97.
Hall, F. P., and Insley, Herbert, compilations of phase-rule diagrams of interest to the ceramist and silicate technologist, (1) 24.
Haller, Percy, random notes on tank practice, (11) 350.
Hansen, J. E. (ed.), Manual of porcelain enameling, (4) 113; W. N. Noble cited on process control, (3) 90.
Harkort, H., effect of particle size of quartz on properties of whiteware bodies, (1) 1; method of testing crazing of whiteware, (12) 359.
Harman, C. G., clay technology as applied to enamels, (9) 255; laboratory experiments, 1939–1940, (4) 98; some characteristics of Ill. pottery clay, (4) 98.
Harman, C. G., and Fraulini, F., properties of kaolinite as function of particle size, (9) 253.
Harman, C. G., and Parmelee, C. W., testing and classification of ball clays, thermal history, (3) 72.
Harrison, H. C., cyanite-clay refractories, I, (6) 181.
Harrison, W. N., tentative tests for abrasion resistance, (12) 366.
Hatch, T., determination of average particle size from screen analysis of nonuniform particulate substances, (1) 4.
Hatch, T., and Choate, S. P., statistical description of size properties of nonuniform particulate substances, (1) 4.
Hatschek, Emil, general theory of viscosity of two-phase systems, (5) 151; Viskosität der Dispersoide, (5) 151.
Hauser, E. A., Colloidal phenomena, (1) 6.
Hauser, E. A., and LeBeau, D. S., studies in colloidal clays, II, (4) 116.
Hauser, E. A., and Reed, C. E., studies in thixotropy, thixotropic behavior and structure of bentonite, II, (5) 151.
Hecht, H., Textbook on ceramics, (2) 62.
Hedvall, J. A., Reaktionsfähigkeit fester Stoffe, (7) 197, (10) 308.
Hedvall, J. A., Alfredsson, S., Ohlsson, K., Runehagen, O., Waldenström, S., and Åkerström, A., reactivity and effects of lattice distortion in important glass-technical and ceramic systems, (10) 313.
Hedvall, J. A., and Cohn, Gunther, reactions in solid state, (10) 308.
Hedvall, J. A., Garping, E., Lindekrantz, N., and Nelson, L., role of ions and crystallographic transformation in reactions in solid state, (10) 313.
Hedvall, J. A., and Ny, V., double decomposition in solid state between synthetic or mineral ferrochromite and magnesium oxide or magnesium carbonate, (10) 313.
Hedvall, J. A., and Sandberg, S. O., reactions in solid state of mixtures of active Fe_2O_3 and CaO, (10) 312.
Henry, D. C., cataphoresis of suspended particles, equation of cataphoresis, I, (4) 117.
Henry, E. C., and Taylor, N. W., acid and base binding capacities and viscosity relations in certain whiteware clays, (4) 98.
Herman, A., factors influencing autoclave chemical durability tests of glass containers, (2) 53.
Hermann, S., innovations in realm of silicon compounds, (10) 293.
Heubach, A. R., light green chromium stains, (6) 169.
Heusler, O., remarks on equilibrium during reduction of chromium sesquioxide and uranium dioxide by means of carbon and effect of nitrogen on uranium carbide, (10) 296.
Hild, K., formation of spinel Al_2ZnO_4 by reaction in solid state, (10) 308.
Hill, E. C., data on development of terra cotta glazes, (8) 234.
Hillebrand, W. F., and Lundell, G. E. F., Applied inorganic analysis, (10) 295.
Hillier, James, electron microscope in determination of particle-size characteristics, (1) 2.
Hodgman, C. D., Handbook of chemistry and physics, (1) 24.
Höegh, E. v., and Goerz, C. P., lens for optical purposes, (6) 193.
Hoffman, M. K., and Barth, J. A. (ed.), Dictionary of inorganic chemical reactions, (1) 24.
Holland, A. J., and Preston, Eric, microscopical examination and identification of crystalline products in commercial glasses, I–II, (11) 330.
Holscher, H. H., effects of autoclave treatments on ceramic bodies and glazes, (12) 355; expansion of ceramic bodies caused by liquid and vapor penetration, (12) 355.
Hopkinson, J., electrostatic capacity of glass, (2) 34.
Hovestadt, H., Jena glass and its scientific and industrial applications, (2) 58, (4) 121, (11) 354.
Howe, E. E., and Fellows, R. L., effect of manganese, nickel, and cobalt oxide on adherence and reboiling properties of ground-coat enamels, (11) 351.
Hüttig, G. F., and Frantz, E., "memory" of solid materials, (7) 198.
Hüttig, G. F., and Kölbl, F., active oxides, aluminum oxides and their addition compounds with water, LXVII, (7) 198.
Hüttig, G. F., Tschakert, H. E., and Kittel, H., investigation on course of zinc ferrite formation from zinc oxide and iron oxide, (10) 314.
Hüttig, G. F., Zinker, D., and Kittel, H., active stages encountered during transformation of mixture of metal oxides into chemical combination, (10) 314.
Hugill, W., preparation and properties of some synthetic spinels, (7) 198.
Hugill, W., and Green, A. T., some factors influencing durability of chrome-magnesite brick in basic open-hearth steelmaking furnaces, (7) 202.
Huggins, M. L., density of silicate glasses as function of composition, (1) 11, (1) 13; dispersion of silicate glasses as function of composition, (1) 16; refractive index of silicate glasses as function of composition, (1) 15; silicate glasses, calculation of density, (9) 262.
Huggins, M. L., and Sun, K.-H., calculation of density and optical constants of glass from composition in weight percentage, (1) 10, (1) 13, (9) 262; changes of properties of glass resulting from changes of composition, (1) 17.
Huggins, M. L., Sun, K.-H., and Davis, D. O., dispersion of silicate glasses as function of composition, II, (1) 16.
Hull, A. W., and Berger, E. E., glass-to-metal seals, (3) 88.
Hunter, R. S., instructions for use of Hunter multipurpose reflectometer, (6) 165; multipurpose photoelectric reflectometer, (6) 166.
Hurst, T. L., and Andrews, A. I., study of effect of soluble salts present in enamel mill liquors, (1) 25.
Hutchison, Clark, effect of various factors on abrasive resistance of porcelain enamels, (12) 366.

Insley, Herbert, determination of source and means of prevention of stones in glass, (11) 330; petrographic microscope as instrument for glass technologist, (11) 350; study of origin of stones in glass, (11) 330.
International Critical Tables, Vol. I, (11) 350; Vol. IV, (1) 24.
Irwin, J. T., and Bevis, R. E., modification of the Bingham plastometer, (4) 98.

Jander, W., reactions in solid state, course of reactions in solid state, II, (7) 198; reactions in solid state at high temperatures, tricalcium silicate, most important constituent of Portland cement clinker, XVIII, (10) 312.
Jander, W., and Bunde, K., reactions in solid state at high temperatures, intermediate steps in formation of zinc aluminate from zinc oxide and aluminum oxide in solid state, XIV, (10) 315.
Jander, W., and Hermann, H., reactions in solid state at high temperatures, theory of active form which appears at beginning of reaction in solid state, XXIII, (7) 198, (10) 314.
Jander, W., and Hoffman, E., reactions in solid state at high temperatures, reaction between CaO and SiO_2, XI, (7) 198.
Jebsen-Marwedel, H., chemistry of glass-furnace construction, slagging processes above metal line, I, (11) 350; influence of surface tension of slag glasses from refractory materials on their tendencies to form cords and streaks, (5) 143; remarks on influence of surface tension in glassmelting processes, (5) 143.
Jefferys, Harold, draining of a vertical plate, (7) 203.
Jeffrey, G. B., motion of ellipsoidal particles immersed in viscous fluid, (5) 152.
Jenkins, F. A., and White, H. E., Fundamentals of physical optics (on Fresnal equations), (5) 145.
Jenny, Hans, and Reitemeier, R. F., electrokinetic properties in relation to base-exchange phenomena, (4) 116.
Jevons, W., band spectra of silicon oxide and chloride, and chlorides of carbon, boron, and aluminum, (10) 294; ultraviolet band-system of carbon monosulfide and its relation to those of carbon monoxide ("4th positive" bands) and silicon monoxide, (10) 294.
Johannsen, Albert, Manual of petrographic methods, (11) 330.
Johnson, A. L., and Lawrence, W. G., fundamental study of clay, surface area and effect on exchange capacity of kaolinite, IV, (3) 77.
Johnson, A. L., and Norton, F. H., fundamental study of clay: preparation of purified kaolinite suspension, I, (3) 77, (4) 117, (5) 158; mechanism of deflocculation in clay–water system, II, (4) 98.
Johnson, P. D., suggestion for tetrahedral packing, (5) 153.
Jost, Wilhelm, Diffusion und chemische Reaktion in festen Stoffen, (7) 197, (10) 308.

Joule, J. P., drift in ice-point readings, (2) 57.
Judd, D. B., and Kelly, K. L., method of designating colors, (6) 165.
Juran, J. M., A, B, C of quality control, (12) 377.

Kautz, Karl, discussion on Lord's paper, (2) 46.
Keller, F., dielectric losses of glasses of different composition, (2) 33.
Keller, H., cited on high-frequency materials, (6) 176; curves for variation of dissipation factor with frequency, (6) 177.
Keller, W. D., P. C. E. of coarse-grained refractories, (8) 241.
Kelley, O. J., and Shaw, B. T., studies of clay particles with electron microscope, hydrodynamic considerations in relation to shape of particles, III, (3) 77.
Kelley, W. P., modern clay researches in relation to agriculture, (4) 116.
Kelley, W. P., and Jenny, H., relation of crystal structure to base exchange and its bearing on base exchange in soils, (1) 6.
Keppeler, Gustav, surface tension of glass, (6) 186.
Kerr, P. F., decade of research on nature of clay, (9) 253.
King, B. W., Jr., effect of particle size and index of refraction on reflectance, (9) 258.
King, R. M., mechanics of enamel adherence: role of cobalt oxide in metal and oxide precipitation during ground-coat firing cycle and determination of temperature and time intervals of precipitation, XIV, (11) 350; influence of cobalt and nickel oxides on metal precipitation at ground coat-iron interface, XV, (11) 350.
Klein, A., improved hydrometer for use in fineness determinations, (1) 2.
Klemm, W., and Grimm, L., lower vanadium oxides, (10) 297.
Klinefelter, T. A., and Meyer, W. W., properties of American kaolins and comparison with English china clays, (4) 97.
Klinefelter, T. A., Meyer, W. W., and Vachuska, E. J., some properties of English china clay, (4) 97.
Knapp, Oscar, optical glass, (4) 121.
Koch, E., and Wagner, Carl, formation of Ag_2HgI_4 from AgI and HgI_2 by reaction in solid state, (10) 311.
Koenig, C. J., low-temperature vitreous bodies, (12) 359; nepheline syenite in low-temperature vitreous ware, (12) 360.
Koenig, C. J., and Watts, A. S., durability of tableware decorations, (2) 64.
Koenig, J. H., particle-size distribution of ingredients versus body properties, (1) 2.
Koenig, J. H., and Henderson, F. C., particle-size distribution of glazes, (1) 2.
Körber, F., and Oelsen, W., reactions of chromium with acid slags, (10) 296.
Kolthoff, I. M., and Carr, C. W., studies on aging and coprecipitation, distribution coefficient of arsenate between magnesium ammonium phosphate and solution, XXXVII, (10) 312.
Kondo, S., and Suzuki, S., talc porcelain, (2) 39.
Kondo, S., and Yamauchi, T., inversion of quartz to tridymite, IX–X, (10) 286.
Konopicky, K., and Caesar, F., science of chrome ores, degree of oxidation of iron in chrome ores, III, (7) 202.
Kozeny, Josef, über Kapillare Leitung des Wassers im Boden (Aufstieg, Versickerung, und Anwendung auf die Bewässerung), (11) 319.
Krause, Otto, relationships between grain size of quartz and properties of hard porcelain, I–II, (1) 1.
Kreidl, N. J., possibilities of strontia in ceramics, (8) 234.
Kreimer, G. S., simultaneous reduction of oxides of iron, titanium, and columbium with aluminum, (10) 296.
Kriegel, W. W., summary of occurrence, properties, and uses of vermiculite at Libby, Mont., (2) 50.
Kubelka, P., and Munk, F., Beitrag zur Optik der Farbenstriche, (9) 258.

Landolt, H., and Börnstein, R., Physikalisch-Chemische Tabellen, (1) 23.
Lange, L. A., effect of sodium nitrite in cover enamels, (1) 25.
Lange, N. A., and Forker, G. M., Handbook of chemistry and physics, (1) 24.
Langmuir, I., dissociation of solids and kinetic interpretation of phase rule, (1) 4.
Larsen, E. S., microscopic determination of nonopaque minerals, (11) 330.
Latimer, W. M., and Hildebrand, J. H., Reference book of inorganic chemistry, (10) 294.
Lea, F. M., and Desch, C. H., Chemistry of Portland cement and concrete, (7) 199.
Lemaire, F. E., monoxide of silicon, (10) 293.
Lester, W. R., influence of silica stones on strength of glass containers, (11) 350; use of polarizing microscope in factory control, (3) 85.
Lewis, W. K., Squires, Lombard, and Broughton, Geoffrey, Industrial chemistry of colloidal and amorphous materials, (5) 135.
Lillie, H. R., expansion characteristics of Corning 96% silica glass No. 790, (10) 301; high-temperature viscosities of soda-silica glasses, (5) 129; Margule's method of measuring viscosities modified to give absolute values, (5) 129; measurement of absolute viscosity by use of concentric cylinders, (5) 129; viscosity of glass between strain point and melting temperature, (5) 129, (10) 301; viscosity measurements in glass, (5) 129.
Lin, C.-Y., effect of various catalysts on conversion of quartz to cristobalite and tridymite at high temperatures, (10) 287.
Lintz, E. H., use of talc and pyrophyllite in semivitreous dinnerware bodies, (12) 355.
Littleton, J. T., method for measuring softening temperature of glasses, (5) 133.
Littleton, J. T., and Morey, G. W., Electrical properties of glass, (2) 39.
Löfquist, H., microscopic studies on slag inclusions in iron and steel, (10) 296.
Loomis, G. A., grain size of whiteware clays as determined by Andreasen pipette, (1) 2, (9) 253; properties of clay casting slip, (4) 98.
Lord, J. O., critical analysis of some statements and experiments on adherence of sheet-steel ground coats, (2) 46.

Macey, H. H., clay-water relationships and internal mechanisms of drying, VI, (3) 79.
Macey, H. H., and Clewe, F. H., measurement of apparent porosity, (2) 35.
Maclaurin, R. C., intensity of light reflected from transparent substances, (5) 145.
MacMichael, R. F., testing clay, (4) 98.
Maier, C. G., sponge chromium, (10) 296.
Markert, F. S., function of manganese dioxide in ground coat, (11) 351.
Marshall, C. E., Colloids in agriculture, (1) 24.
Martin, Geoffrey, and Bowes, E. A., researches on theory of fine grinding, IX–X, (1) 4.
Martin, S. W., determination of subsieve particle-size distributions by sedimentation methods, (1) 2.
McAdams, W. H., Heat transmission, (2) 51.
McCollom, P. C., and Danielson, R. R., effect of firing treatment on physical properties of dry-process enamels, (12) 366.
McDowell, C. M., and Usher, F. L., viscosity and rigidity in suspensions of fine particles, aqueous suspensions, I, (5) 151; nonaqueous suspensions, II, (5) 161.
McGee, E. N., silica cement, (8) 241.
McIntyre, G. H., and Irwin, J. T., application of Gardner mobilometer to enamel-slip consistency studies and control, (4) 98.
McMaster, Harold, variations of refractive index of glass with time and temperature in annealing region, (9) 267.
McVay, T. N., Galbreath, W. W., Jr., and Allen, Dan, raw topaz as a high-temperature bond for domestic kyanite, (8) 241.
McVay, T. N., and Wilson, Hewitt, substitution of topaz, domestic kyanite, and synthetic mullite-corundum for India kyanite, I–III, (6) 185, (9) 275.
Mellor, J. W., Comprehensive treatise on inorganic and theoretical chemistry, Part 2, carbon, silicates, Vol. VI, (10) 294; Vol. IX, (1) 24; crazing and peeling of glazes, (12) 359; discussion of C. E. Ramsden, "notes on chromium glazes," (6) 174.
Merwin, H. E., optical properties and theory of color of pigments and paints, (6) 168; system MgO–FeO–Fe_2O_3 in air at one atmosphere, (6) 173.
Meyer, O., course of reactions between graphite and oxides, especially between heavy metallic carbides and oxide, (10) 296.
Milbauer, J., action of oxygen on metallic oxides at high temperature and pressure, (6) 169.
Mills, R. H., influence of some unusual zinc compounds in chrome green glaze, (6) 174.
Mitchell, Lane, and Henry, E. C., nature of Ga. kaolins, I–II, (9) 253.
Monack, A. J., and Beeton, E. E., analysis of strains and stress in glass, I–IV, (3) 87.
Mooney, Melvin, electrophoresis and the diffuse ionic layer, (4) 117.
Morey, G. W., devitrification of soda-lime-silica glasses, (11) 344; effect of magnesia on devitrification of soda-lime-silica glass, (8) 222; Properties of glass, (4) 121, (9) 261, (11) 340.
Morey, G. W., and Bowen, N. L., ternary system sodium metasilicate–calcium metasilicate–silica, (3) 83.
Morgan, S. O., dielectric behavior of some ceramic materials, (2) 33.
Mott, N. F., and Gurney, R. W., Electronic processes in ionic crystals, (10) 311.
Moullin, E. B., molecular nature of a dielectric, (6) 175.
Müller, H., theory of electrophoretic migration, (4) 110; zur allgemeinen Theorie der rachen Koagulation, (3) 77.
Mulliken, R. S., isotope effect of band spectra, I, (10) 297; spectrum of boron monoxide, II, (10) 297.
Murgatroyd, J. B., significance of surface marks on fractured glass, (3) 86.

Nacken, R., and Grunewald, M. E., chemical combinations of lime and magnesia with ferric oxide, (7) 198.
Nargund, K. S., and Watson, H. E., reactions of chromates at high temperatures, system lime–chromium oxide–oxygen, II, (6) 169.
Noble, W. N., "process control" in Manual of porcelain enameling, (3) 90.
Noda, Tokiti, and Hasegawa, Masotosi, effect of addition of salt vapor on synthesis and crystal growth of spinel, (7) 198.
Northrup, J. N., and Kunitz, M., improved type of electrocataphoresis cell, (4) 116.
Norton, F. H., critical study of differential thermal method for identification of clay minerals, (3) 68; measuring viscosity of glass, (5) 129.
Norton, F. H., and Speil, S., fractionation of clay into closely monodispersed systems, (3) 77, (4) 117; measurement of particle sizes in clay, (4) 117.
Noyes, Bradford, circuit for temperature controls, (2) 58.

O'Meara, R. G., Norman, J. E., and Hammond, W. E., froth flotation and agglomerate tabling of feldspars, (1) 6.
Orcel, Jean, differential thermal analysis for determination of constituents of clays, laterites, and bauxites, (3) 68.
Owens-Illinois Glass Co. General Research Laboratory, effect of barium oxide and zinc oxide on properties of soda-dolomite lime-silica glass, (8) 221, (12) 370; effect of iron oxide on properties of soda-dolomite lime-silica glass, (8) 221.
Owens, J. S., and Emanuel, E. C., effect of storage conditions on weathering of commercial glass containers, (5) 157.

Palmer, W. E., influence of flint particle size on permanent moisture and thermal expansion in porous earthenware bodies, (12) 355.
Pardee, J. T., Glass, J. J., and Stevens, R. E., massive low-fluorine topaz from Brewer Mine, S. C., (6) 181.
Parmelee, C. W., and Ally, Abde, some properties of chrome spinel, (7) 199.
Parmelee, C. W., and Amberg, C. R., solubility of quartz and clay in feldspar, (2) 40.
Parmelee, C. W., Badger, A. E., and Ballam, George, study of group of typical spinels, (7) 198.
Parmelee, C. W., and Harman, C. G., effect of alumina on surface tension of molten glass, (6) 186; surface tensions of molten glasses, surface tensions of soda-lime-silica melts, II, (6) 186, (7) 205.
Parmelee, C. W., and Lyon, K. C., surface tensions of molten glasses, surface tension of molten glass, I, (6) 186.
Parmelee, C. W., and Monack, A. J., devitrification of glass, relative stabilities of different glasses, time-temperature curves of

visible devitrification, and proposed classification of glasses, (11) 350.
Parmelee, C. W., and Morgan, W. R., effect of fineness of flint on vitrification of a ceramic body, (1) 1.
Parmelee, C. W., and Shaw, D. T., effect of additions of CaO and MgO on enamel glasses, (11) 354.
Partridge, J. H., effect of gases on commercial glass containing lead oxide, (11) 350.
Peck, A. B., new glass stone, $Na_2O \cdot 3CaO \cdot 6SiO_2$, (11) 330.
Peddle, C. J., development of various types of glass, VI–IX, (11) 350; comparison of alkali-lime-silica and alkali-lead oxide-silica glasses, X, (11) 350.
Percy, J., president's address, (10) 298.
Peskin, W. L., effect of furnace atmosphere on colors derived from chromic oxide, (6) 165.
Pfund, A. H., Brewsterian angle and refractive indices, (5) 147.
Phelps, G. W., notes on casting, (4) 98.
Piccolpasso, C., Potters art, (2) 62.
Pierce, R. H. H., Jr., and Austin, J. B., comparison of thermal expansion of used silica brick from insulated and uninsulated open-hearth furnace roof, (10) 286.
Pillai, D. S., effect of zinc oxide on coloring properties of chromium, cobalt, and iron oxides, (6) 174.
Pole, G. R., and Taylor, N. W., kinetics of solid-phase reactions of certain carbonates with mullite, silica, and alumina, (7) 197.
Porcelain Enamel Institute, test for acid resistance of porcelain enamel, flatware, I, (12) 368; test for resistance of porcelain enamels to surface abrasion, (12) 367.
Posnjak, E., crystal structures of magnesium, zinc, and cadmium ferrites, (6) 173.
Potter, H. N., method of making silicon monoxide, (10) 293; Monox, (10) 293; process of producing silicon monoxide, (10) 293; production of "Monox," new electric furnace product, (10) 293; silicon monoxide, (10) 293.
Potts, J. C., comparison of rates of melting glasses made from sodium carbonate, dolomite, limestone, and silica sand, (8) 225; melting rate of soda-lime-silica glasses as influenced by composition and effect of minor constituents, (8) 225.
Preston, Eric, crystallization relationship of soda-lime-magnesia-silica glass as used for drawn sheet and process of devitrification, (11) 350.
Preston, Eric, and Turner, W. E. S., fundamental studies of glassmelting process, effect of particle size and temperature on rate of glass formation of pure soda-lime-silica glass, (11) 350.
Preston, F. W., bottle breakage, causes and types of fractures, (3) 86; propagation of fissures in glass and other bodies with special reference to split-wave front, (3) 86; study of rupture of glass, (3) 86.
Proctor, R. F., and Douglas, R. W., measurement of viscosity of glass at high temperatures by rotating cylinder viscometry, (5) 154.
Purdy, R. C., and Brown, G. H., study of chromium tin pinks, (6) 174.

Quincke, G., cited on electroosmotic flow of liquids in cell, (4) 116.

Rait, J. R., viscosity of slags and glasses, I–II, (5) 150.
Ramsden, C. E., study of chromium red glaze, (8) 234.
Rankin, G. A., and Merwin, H. E., ternary system $MgO–Al_2O_3–SiO_2$, (7) 199, (11) 327.
Rayleigh, Lord, collected papers, (5) 145; polished surfaces of black glass, (5) 145.
Rees, W. J., use of Indian sillimanite, (6) 181.
Reimers, J. C., application of hydrometer method of fineness analysis to porcelain enamel slips, (1) 3.
Richardson, E. G., some physical properties of clay, (5) 153.
Riddle, F. H., andalusite as a refractory, (6) 181.
Rigby, G. R., Dodd, A. E., White, R. P., and Green, A. T., investigation of permanent expansion of silica products containing cristobalite, (10) 287.
Rigterink, M. D., improved ceramic dielectric materials, (2) 33, (10) 301.
Rigterink, M. D., Grisdale, R. O., and Morgan, S. O., relation between chemical composition and dielectric properties of ceramic materials with low dielectric losses, (2) 39.
Robinson, W. G., ceramic insulations for high-frequency work, (6) 176.
Robinson, W. O., determination of organic matter in soils by hydrogen peroxide, (4) 101.
Rodden, C. J., removal of static charges from glassware by ultraviolet light, (10) 303.
Rogers, A. F., and Kerr, P. F., Thin section mineralogy, (1) 24, (3) 88; Optical mineralogy, 2d ed., (11) 350.
Roller, P. S., classification of methods of mechanical analysis of particulate materials, (1) 2; law of size of distribution and statistical description of particulate materials, (1) 4.
Roller, P. S., and Roundy, P. V., Jr., surface area of Portland cement, (1) 2.
Rosenberg, J. E., and Langerman, A., method and apparatus for studying physical properties of vitreous enamels on steel, (11) 352; tearing of vitreous enamels, (1) 25.
Russell, Ralston, Jr., development of superduty refractories from Ohio, Pa., and Ky. fire clays, (4) 112.

Sands, J. W., Invar, Elinvar, and related iron-nickel alloys, (10) 304.
Saper, P. G., rotational analysis of ultraviolet bands of silicon monoxide, (10) 294; ultraviolet bands of SiO, (10) 294.
Satterly, John, and Givens, H., shape of liquid film draining on vertical, clean wetted glass plate and combined effects of gravity, viscosity, surface tension, and evaporation on same, III, (7) 203.
Saunders, J. B., expansivity of a Vycor-brand glass, (10) 301.
Sauveur, Albert, Metallography and heat-treatment of iron and steel, (11) 336.
Schade, W., photographic objective, (6) 194.
Schober, Rolf, and Tilo, Erich, chemical investigation of silicates, topax, Al_2SiO_4 (F, OH, O) and its synthesis and a new aluminum oxide containing fluorine, (6) 183.
Scholes, S. R., rapid method for estimation of soda in glasses, (5) 148.
Schott, E., high-frequency losses in glasses and other dielectrics, (2) 34.
Schottky, W., mechanism of ionic motion in solid electrolytes, (10) 311.
Schramm, Edward, and Hall, F. P., notes on casting slip, (4) 97.
Schurecht, H. G., relation of salt to clay in purification of clays, (4) 98.
Schurecht, H. G., and Pole, G. R., effect of water in expanding ceramic bodies of different compositions, (12) 355; methods for measuring strains between glazes and ceramic bodies, (8) 236, (12) 355; moisture expansion of glazes and other ceramic bodies, (12) 355.
Schwarz, H., cited on effect of relative humidity on dissipation factor of insulating materials, (6) 177.
Schweyer, H. E., particle-size studies, (1) 7.
Schweyer, H. E., and Work, L. T., methods for determining particle-size distribution, (1) 2.
Scott, W. W., Standard methods of chemical analysis, Vol. II, (10) 305.
Seil, G. E., refractories from metallurgical viewpoint, (11) 327.
Seil, G. E., and Staff, orthosilicates of alkaline earths with special reference to their uses in the refractory field, (7) 198; bibliography, (7) 200.
Shearer, W. L., control of plasticities of ceramic slips, (4) 98.
Shewart, W. A., Economic control of quality of manufactured product, (12) 374.
Silverman, W. B., effect of alumina on devitrification of soda-lime-silica glasses, (3) 81, (8) 221, (11) 340; effect of alumina on devitrification of sodium oxide-dolomite lime-silica glasses, (3) 83, (8) 221, (11) 340; effect of alumina on expansion and deformation temperatures of soda-lime-silica glasses, (8) 221; surface tension of glass and its effect on cords, (5) 143, (6) 186.
Simon, L. E., Engineer's manual of statistical methods, (12) 374.
Smail, G. G., Brooksbank, R. J., and Thornton, W. M., electrical resistance of moisture films on glazed surfaces, (6) 180.
Smoluchowski, M., Handbuch der Electricität und des Magnetisimus, (4) 116.
Smyth, C. P., Dielectric constant and molecular structure, (6) 175.
Sosman, R. B., properties of silica, (10) 286, (10) 298, (10) 302.
Soyck, Wener, Eigentümlichkeiten des dielektrischen Verhaltens rutilhaltiger Kondensator Baustoffe, (6) 179.
Speil, S., effect of adsorbed electrolytes on properties of monodisperse clay–water systems, (4) 98.
Spencer, S. D., do glass rods and tubes bend under their own weight, (11) 352.
Sproat, I. E., Treischel, C. C., and Emrich, E. W., all-American sanitary-ware body, (4) 98; use of organic dispersing agents in casting slips, (4) 98.
Starke, K., surface of catalytic mixtures and surface changes caused by reaction in solid state, (10) 315.
Stott, V. H., Turner, D., and Sloman, H. A., effect of thermal treatment of glass by precise viscometry, (7) 203.
Stuckert, L., stannic oxide as opacifier in wet enamels, (4) 113.
Stuckey, J. L., and Amero, J. J., physical properties of massive topaz, (6) 181.
Swicker, V. C., ring-section examination of glass containers, (3) 85.

Tammann, G., transformations in crystals with lattice defects, (7) 198.
Taylor, N. W., elastic aftereffects and dielectric absorption in glass, (2) 60; law of annealing of glass, quantitative treatment and theoretical interpretation, (2) 58; reactions in solids in absence of liquid phase, (7) 197.
Taylor, N. W., and Dear, P. S., elastic and viscous properties of several soda-silica glasses in annealing range of temperature, (5) 129.
Taylor, N. W., and Lin, C.-Y., effect of various catalysts on conversion of quartz to cristobalite and tridymite at high temperatures, (10) 286, (11) 350.
Taylor, N. W., McNamara, E. P., and Sherman, J., elastico-viscous properties of soda-lime-silica glass at temperatures near "transformation point," (5) 129.
Taylor, N. W., and Noyes, Bradford, Jr., aging of thermometers, (9) 267.
Thiemecke, H., thermal and moisture expansion of ball clays and bodies at different temperatures, (12) 355; thermal and moisture expansion of kaolins and bodies at different temperatures, (12) 355.
Thompson, C. L., identification of stones in glass, (11) 330.
Thoreen, R. C., comments on hydrometer method of mechanical analysis, (1) 6.
Thurnauer, Hans, review of ceramic materials for high-frequency insulation, (2) 33.
Thurnauer, Hans, and Badger, A. E., dielectric loss of glass at high frequencies, (2) 36.
Thurnauer, Hans, and Rodriguez, A. R., notes on constitution of steatite, (2) 35.
Tiede, R. L., and Tooley, F. V., effect of temperature on homogenizing rate of soda-lime-silica glass, (9) 264.
Tool, A. Q., and Insley, Herbert, crystalline silica in certain devitrified glasses, (10) 286.
Tooley, F. V., and Greene, J. F., personal communication, (10) 305.
Tooley, F. V., and Tiede, R. L., factors affecting degree of homogeneity of glass, (9) 264.
Tone, F. J., production of silicon in electric furnace, (10) 293.
Trostel, L. J., absorption of magnesia by chromite spinel, (7) 202.
Turnbull, J. C., separation of inhomogeneities in bottle glass by density differences, (2) 42, (9) 263.
Turnbull, J. C., and Ghering, L. G., cord analysis, (2) 42, (9) 263.

U. S. Ordnance Dept., Document No. 2037, manufacture of optical glass and optical systems, (11) 352.

Van Nieuwenburg, C. J., and Zijlstra, H. J., dilatometric measurements on tridymite and cristobalite, (10) 286.
Vasenin, I. F., reciprocal action of CaO and Cr_2O_3 on heating, (6) 169.
Vaughan, T. C., determination of density by flotation method, (9) 263.

Wagner, Carl, mechanism of formation of ionic compounds of high order (double salts, spinels, silicates), (10) 310; theory of arranged mixed phases, disarranged phenomena in polar compounds as basis for ionic and electronic conduction, III, (10) 311; theory of tarnishing process, (7) 198; theory of tarnishing process, II, (10) 311.
Wagner, Carl, and Schottky, W., theory of arranged mixed phases, I–II, (10) 311.
Washburn, E. W., and Shelton, G. R., viscosities and surface tensions of soda-lime-silica glasses at high temperatures, viscosities of glasses at high temperatures, I, (5) 134.
Waterton, S. C., viscous-temperature relation and some inferences on nature of molten and plastic glass, (5) 138.
Watkins, R. T., degree to which different glaze compositions take vapor lusters, (2) 64.
Watts, A. P., effect of furnace atmospheres on quality of certain types of glazes, (6) 165.
Watts, A. S., citation of unpublished work on $SrO–Al_2O_3–SiO_2$ system, (8) 234.
Weber, R., über den Einfluss der Zusammensetzung des Glases auf die Veranderungen des Nullpunkts, (2) 58.
Weil, R., microscopic study of alpha-beta transformation of natural cristobalite, (10) 286.
Weiser, H. B., Colloid chemistry, (1) 24.
Weltmann, R. N., and Green, H., rheological properties of colloidal solutions, pigment suspensions, and oil mixtures, (5) 151.
Westman, A. E. R., effect of mechanical pressure on imbibitional and drying properties of some ceramic clays, I, (3) 79.
Whitesell, R. J., effect of soluble salts on properties of enamels, (1) 25.
Whitney, W. R., General Electric Co., personal communication, (10) 294.
Whittaker, H., effect of particle size on plasticity of kaolinite, (3) 77.
Wiberg, E., "borohydrates" and boron suboxides of Travers, Ray, and Gupta, (10) 297.
Wichers, Edward, Finn, A. N., and Clabaugh, W. S., comparative tests on chemical glassware, (10) 303.
Wiebe, H. F., über die Herstellung von Normalglas für Thermometer, (2) 58.
Wilde, W. T., and Rees, W. J., ternary system $MgO–Al_2O_3–SiO_2$, (11) 327.
Williamson, E. D., and Adams, L. H., temperature distribution in solids during heating or cooling, (9) 272.
Willis, G. A., notes on casting slip in production, (4) 97.
Wilson, G. V., notes on formation of certain rockforming minerals in and about glass furnaces, (11) 330.
Wilson, Hewitt, Ceramics-clay technology, (1) 24.
Wilson, Hewitt, and Page, G. A., simple dispersion test for clays, (4) 98.
Winchell, A. N., Elements of optical mineralogy, Parts I and II, (11) 330; Microscopic characters of artificial inorganic solid substances or artificial minerals, (7) 199; Optic and microscopic characters of artificial minerals, (1) 24.
Winkler, C., reduction of oxides by magnesium, (10) 293.
Winter, Aniuta, structural homogeneity of glass, (9) 266; transformation region of glass, (9) 266.
Winterkorn, H. F., condition of water in porous systems, (3) 80.
Woods, L. H., silicon oxide bands, (10) 294.
Wretblad, P. E., X-ray studies on systems $Fe_2O_3–Cr_2O_3$ and $Fe_2O_3–Mn_2O_3$, (6) 173.
Wright, E. P., study of absorption of two earthenware bodies and their resistance to crazing in steam test, (12) 355.

Young, J. C., density data, (1) 13.
Young, J. C., and Finn, A. N., comparison of two recent studies on refraction and dispersion of glasses, (1) 15; effect of composition and other factors on specific refraction and dispersion of glasses, (1) 15.

Zapffe, C. A., and Sims, C. E., silicon monoxide, (10) 297; silicon-oxygen equilibria in liquid iron, (10) 297.
Zarbo, G. J., Hunt, H. J., and Smith, D. C., analysis of cords and stones, (9) 264.
Zintl, W., Bräuning, W., Grube, H. L., Kringa, W., and Morawietz, W., silicon monoxide, (10) 295.
Zintl, E., and Grube, H., reduction of inorganic oxidic compounds by silicon monoxide, (10) 295.
Zintl, W., Kringa, W., and Bräuning, W., reduction of inorganic compounds by silicon monoxide, (10) 295.
Zintl, E., Morawietz, W., and Gastinger, E., boron monoxide, (10) 297.
Zschacke, F. H., deposits in heat regenerators and waste-gas channels, (10) 297; volatilization of components of glass during melting and fining, (10) 297.

CORRECTIONS

EFFECT OF GLASS ON ALCOHOLIC PRODUCTS STORED IN BOTTLES AT ROOM TEMPERATURE FOR THREE YEARS

By A. Herman and H. L. Shay

Published in *Jour. Amer. Ceram. Soc.*, **27** [2] 53–57 (1944).

The words "decrease" or "decreased" should be substituted for "increase" or "increased" in the following lines:

(1) p. 53 (Abstract), lines 5–6; line 7.
(2) p. 54, Figs. 1 and 2; left column, line 4.
(3) p. 55, Figs. 3 and 4.
(4) p. 56, left column, last paragraph, line 1 and lines 5 and 6.

PARTICLE-SIZE DISTRIBUTION OF STEATITE TALC

By J. S. White

Published *Jour. Amer. Ceram. Soc.*, **27** [11] 320–23 (1944).

Page 323, Fig. 6: The designations "% St'd" and "% Fine" on the scales at the bottom of the graph should be transposed so that the upper scale is designated "% Fine" and the lower "% St'd." The curves will then indicate that the shrinkage is higher when the ultra-fine talc is used, which is actually the case.

TABLE OF CONTENTS

for

Volume 27, 1944

January [No. 1], pp. 1–31

1. R. Russell, Jr., and R. S. Weisz: Some Particulate Characteristics of Commercial Flint and Feldspar 1–7
2. M. F. Goudge: Brucite Magnesia 8–10
3. M. L. Huggins and K.-H. Sun: Changes of Properties of Glass Resulting from Changes of Composition 10–12
4. M. L. Huggins and K.-H. Sun: Glass Properties and the Periodic Table 13–17
5. M. K. Blanchard and A. I. Andrews: Fundamental Properties of Soluble Salts in Enamel Mill Liquors 17–24
6. M. K. Blanchard and A. I. Andrews: Enamel Film Strength as Affected by Properties of Enamel Before, During, and After Drying 25–31

February [No. 2], pp. 33–64

7. H. F. G. Ueltz: Crystalline and Glassy Phases of Steatite Dielectrics 33–39
8. A. G. Johnson and D. B. Underhill: Quantitative Determination of Glassy Phase in a Ceramic Body 40–41
9. F. V. Tooley and R. L. Tiede: Factors Affecting Degree of Homogeneity of Glass 42–45
10. A. I. Andrews and H. R. Swift: Effect of Composition and Temperature on Solubility of Iron Oxide in Ground-Coat Enamel Glass 46–50
11. F. K. Pence and E. B. Blount: Vermiculite as Raw Material in Ceramic Manufacture 50–52
12. A. Herman and H. L. Shay: Effect of Glass on Alcoholic Products Stored in Bottles at Room Temperature for Three Years 53–57
13. N. W. Taylor and Bradford Noyes, Jr.: Aging Thermometers 57–62
14. Forrest Burnham and C. M. Harder: Practical Production of One-Fire Luster Glazed Pottery 62–64

March [No. 3], pp. 65–95

15. R. E. Grim and R. A. Rowland: Differential Thermal Analysis of Clays and Shales, Control and Prospecting Method 65–76
16. F. H. Norton and A. L. Johnson: Fundamental Study of Clay: V, Nature of Water Film in Plastic Clay 77–80
17. J. F. White and W. B. Silverman: Devitrification Characteristics of Alkali-Lead Oxide-Dolomite Lime-Silica Glasses 81–85
18. Glass Container Association of America: Polariscopic Examination of Glass Container Sections 85–89
19. E. C. Seabright: Methods for Testing Cleaner Solutions 90–95

April [No. 4], pp. 97–128

20. Ralston Russell, Jr., and W. C. Mohr: Casting Characteristics of Clays: I, Improved Methods for Determination 97–113
21. F. A. Petersen and A. I. Andrews: Enameled Utensil Manufacturer's Council Tentative Standard Solubility Tests for Porcelain Enameled Cooking Utensils 113–15
22. W. L. Coughanour and J. L. Utter: Cataphoresis of Purified, Fractionated Kaolinite Particles 116–20
23. W. A. Fraser and L. O. Upton: Optical Fluor-Crown Glasses 121–28

May [No. 5], pp. 129–64

24. H. A. Robinson and C. A. Peterson: Viscosity of Recent Container Glass 129–38
25. G. J. Zarbo, H. J. Hunt, and D. C. Smith: Analysis of Cords and Stones 138–42
26. M. A. Knight: Surface Tension and Persistence of Cords in Glass 143–45
27. F. L. Bishop, Jr.: Surface Layer of Sheet Glass 145–48
28. S. R. Scholes and E. deR. Falcão: Rapid Method for Estimating Soda in Glasses, II 148
29. F. H. Norton, A. L. Johnson, and W. G. Lawrence: Fundamental Study of Clay: VI, Flow Properties of Kaolinite-Water Suspensions 149–64

June [No. 6], pp. 165–95

30. W. F. McDevit: Effect of Firing Atmosphere on Development of Colors in Ceramic Glazes 165–75
31. H. H. Hausner: Influence of Humidity on Dielectric Properties of High-Frequency Ceramics 175–81
32. G. R. Pole: Calcination of Topaz Ore in Rotary Kiln 181–85
33. K. C. Lyon: Calculation of Surface Tensions of Glasses 186–89
34. R. Kingslake: Optical Glass from Viewpoint of Lens Designer 189–95

July [No. 7], pp. 197–220

35. V. D. Fréchette and A. I. Andrews: Investigation of Reactions of Simple Magnesia Spinels with Alkaline Earth Orthosilicates in Solid State 197–202
36. C. G. Harman and C. F. Schaefer: Study of Factors Involved in Glaze-Slip Control: I, Glaze-Slip Specifications 202–207
37. C. G. Harman and M. K. Blanchard: II, Correlation of Glaze Thickness with Air Permeability 207–209
38. C. G. Harman and H. C. Johnson: III, Additional Glazes and Improved Technique and Apparatus 209–14
39. C. G. Harman and H. C. Johnson: IV, Practical Uses for Coherence Value and Receptivity Measurements 214–20

August [No. 8], pp. 221–49

40. Owens-Illinois Glass Company, General Research Laboratory: Effect of Substituting MgO for CaO on Properties of Typical Soda-Lime Glasses 221–25
41. J. C. Potts, George Brookover, and O. G. Burch: Melting Rate of Soda-Lime Glasses as Influenced by Grain Sizes of Raw Materials and Additions of Cullet 225–31
42. C. G. Harman: Suggestions for Solution of Difficult Glaze-Fit Problems 231–33
43. E. S. McCutchen: Strontia and Its Properties in Glazes 233–38
44. R. E. Birch and M. P. Hall: Some Factors Affecting P. C. E. of Silica Fire Clay 239–41
45. W. W. Calbreath, Jr., T. N. McVay, and Dan Allen: Lightweight Superduty Kyanite-Topaz Refractory 241–46
46. J. I. Tracey, Jr.: High-Alumina Clays of Pulaski and Saline Counties, Arkansas 246–49

September [No. 9], pp. 253–84

47. B. W. King, Jr., H. D. Carter, and H. C. Draker: Properties of Enamel Slips: I, General Properties of Clays and Enamel Slips 253–60
48. L. G. Ghering and M. A. Knight: Properties and Diagnosis of Cords in Pressed and Blown Glassware 260–66
49. Aniuta Winter: Time Problem in Annealing 266–74
50. T. N. McVay, W. W. Galbreath, Jr., and Dan Allen: Substitution of Topaz, Domestic Kyanite, and Synthetic Mullite-Corundum for India Kyanite: IV, Raw Topaz as High-Temperature Bond for Domestic Kyanite 275–82
51. Edward Schramm: Glost Kiln Refractories 282–84

October [No. 10], pp. 285–316

52. M. D. Beals and Samuel Zerfoss: Volume Change Attending Low-to-High Inversion of Cristobalite 285–92
53. C. A. Zapffe: Conversion of Certain Refractory Oxides to Suboxide Form at High Temperatures 293–98
54. M. E. Nordberg: Properties of Some Vycor-Brand Glasses 299–305
55. H. J. Hunt: Analysis of Batch for Segregation 305–308
56. Gunther Cohn: Significance of Topochemical Factors on Rate of Reactions Between Solid Salts 308–16

November [No. 11], pp. 317–54

57. R. S. Lamar: Particle Shape and Differential Shrinkage of Steatite-Talc Bodies 317–20
58. J. S. White: Particle-Size Distribution of Steatite Talc 320–23
59. C. R. Amberg: Effect of Additions of Diopside on Properties of Wall-Tile Body 324–26
60. H. N. Baumann, Jr.: Fusion Experiments in System $MgO–FeO–Cr_2O_3–Al_2O_3$ 327–29
61. W. L. Fabianic: Glasshouse Stones 330–50
62. R. M. King: Mechanics of Enamel Adherence: XVI, Influence of Manganese Dioxide on Metal Precipitation at Ground Coat-Iron Interface 350–51
63. W. G. Martin and F. W. Lauck: Observations Indicating Absence of Plastic Flow in Glass Coating on Steel 352–54

December [No. 12], pp. 355–87

64. H. Thiemecke: Notes on Moisture Expansion 355–58
65. John Marquis: Cone 01 Glazes for Low-Temperature Vitreous Ware 358–66
66. Clark Hutchison: Abrasion Resistance of Porcelain Enamels 366–69
67. Owens-Illinois Glass Company, General Research Laboratory: Effect of Fluorine and Phosphorus Pentoxide on Properties of Soda-Dolomite Lime-Silica Glass 369–72
68. L. G. Ghering: Refined Method of Control of Cordiness and Workability of Glass During Production, Statistical Control Charts Applied to Daily Measurements of Density 373–87